Theses and Dissertations   1. Thesis and Dissertation Collection, all items

1979-03

Development and time domain validation of a low-order, constant speed, pitch-heave model for the XR-3 surface effect ship

Barnes, Leslie William

Monterey, California. Naval Postgraduate School

http://hdl.handle.net/10945/18685

DEVELOPMENT AND TIME DOMAIN VALIDATION
OF A LOW-ORDER, CONSTANT SPEED, PITCH-HEAVE
MODEL FOR THE XR-3 SURFACE EFFECT SHIP

Leslie William Barnes

NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

Development and Time Domain Validation
of a Low-Order, Constant Speed, Pitch-Heave
Model for the XR-3 Surface Effect Ship

by

Leslie William Barnes

March 1979

Advisor: A. Gerba

APPROVED FOR PUBLIC RELEASE;   DISTRIBUTION UNLIMITED.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Development and Time Domain Validation of a Low-Order, Constant Speed, Pitch-Heave Model for the XR-3 Surface Effect Ship		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis; March 1979
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Leslie William Barnes		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93940		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93940		12. REPORT DATE March 1979
		13. NUMBER OF PAGES 119
14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office) Naval Postgraduate School Monterey, CA 93940		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

surface effect ship
XR-3
linear model
heave-pitch dynamics

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

An improved and simplified model for the Heave-Pitch dynamics of the XR-3 CAB Surface Effect Ship is developed for constant speed operation. The nonlinear equations of motion are linearized about the steady-state operating point. Time-domain validation is accomplished by comparison with the 6 DOF model. A signal flow graph of the craft dynamics is developed and Mason's Gain Rule used to determine the characteristic

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE
1 JAN 73
(Page 1)   S/N 0102-014-6601 |

S-Domain polynomials describing the craft's vertical
plane dynamic behavior, with Bode Plot analysis included.
Conclusions are drawn and recommendations for further
study are made.

DEVELOPMENT AND TIME DOMAIN VALIDATION OF A LOW-ORDER,
CONSTANT SPEED, PITCH-HEAVE MODEL FOR THE XR-3 SURFACE
EFFECT SHIP

by

Leslie William Barnes
Lieutenant, United States Navy
B.S.E.E., University of New Mexico, 1972

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN ELECTRICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL

March 1979

ABSTRACT

An improved and simplified model for the Heave-Pitch dynamics of the XR-3 CAB Surface Effect Ship is developed for constant speed operation. The nonlinear equations of motion are linearized about the steady-state operating point. Time-domain validation is accomplished by comparison with the 6 DOF model. A signal flow graph of the craft dynamics is developed and Mason's Gain Rule used to determine the characteristic S-Domain polynomials describing the craft's vertical plane dynamic behavior, with Bode Plot analysis included. Conclusions are drawn and recommendations for further study are made.

TABLE OF CONTENTS

LIST OF FIGURES

ACKNOWLEDGEMENTS

The Author wishes to acknowledge his gratitude to the many persons to whom he is indebted for their assistance in the completion of this work.

A special note of appreciation is extended to Associate Proffessor Alex Gerba Jr., not only for his encouragement and assistance, but also for sharing with the author his insight into many areas of control engineering, modeling, and design philosophy.

Finally, to my wife, Marianne, special gratitude for the patience and encouragement she has provided to help me through this period.

I. INTRODUCTION

In 1973 Leo and Boncal [1] converted the Oceanics Inc. 6 DOF Loads and Motions digital computer simulation program for the 100-B Surface Effect Ship to reflect the physical characteristics of the XR-3 craft. Since that time there has been a continuous effort at the NPS to update and improve on this simulation [2,3,4,5].

One of the major drawbacks of that program which precludes regular use of it for sea state operations simulation is the excessive computational and turn-around times required [6]. As it is presently desired to use the 6 DOF simulation for design and evaluation studies of the proposed 3K Ton SES control System in varying sea state conditions, it is important to significantly reduce the simulation's computational time.

One area where the possibility exists to achieve a major reduction in computational time is the manner in which sidewall forces and moments are calculated. The present form of the 6 DOF program uses a large number of discrete sections (28 per sidewall) with an off-line table look-up scheme to determine the forces generated in each discrete section. The simple model derived by McIntyre [7] uses two sections per sidewall with very simplified geometry that permits on-line computation of the forces and moments. The result of eventual incorporation of this sidewall geometry and forces calculation into the 6 DOF program should be a significant reduction of computation and turn-around time.

Another area of great interest in SES Simulation is

gaining insight into the dynamic behavior of the craft's vertical motion of pitch and heave due to pressure induced lift forces generated in the plenum and seals. As stated in ref [8] as recently as August, 1978,

''The overall precision of the analysis is satisfactory for predicting stability and maneuverability. However, several areas present very complex or difficult physical phenomena to analyze and further effort should be invested to improve understanding of these.''

The first area for continuing investigation recommended was;

''A better determination of pitch-heave dynamic characteristics.''

An improved knowledge of the dynamic characteristics brought about by the pressure induced forces and moments could lead to a reduction of the computation time required for craft simulation. These pressure effects introduce a stiffening in the integration of sea state induced oscillations and a better understanding of processes could lead to the removal of this stiffness and thus reduced CPU time.

In this work both of these areas are considered. First of all the various craft physical characteristics are modeled, resulting in changes and improvements to the initial efforts by McIntyre [7]. These equations are linearized about a steady-state operating point using the Taylor Series expansion. The linearized equations are cast into a State Space format and simulated on the digital computer. Comparison is made between the time-domain results of the linear model and the 6 DOF model. The State Space representation is used to generate a signal flow graph. Mason's Gain Rule is

applied and the S-domain roots of the craft's characteristic equations are located and it is shown that some simplification and reduction of system order is possible. The resultant S-domain polynomials are used to generate Bode Plots to graphically display the craft's simplified frequency response.

Conclusions are drawn and recommendations are made concerning the validity of the model and areas for future study.

Several procedural notes are in order. Because all equations are to be solved digitally using the FORTRAN computer language and because digital computer text processing facilities were used to generate this document, all formulas will be presented in FORTRAN format. In the thesis body reference to the ''nonlinear model'', ''six degree-of -freedom model'' or ''6 DOF'' model all mean the Loads and Motions program as adapted to the XR-3 test craft at the Naval Postgraduate School [3]. Reference to the linear model refers to the linearized model of the same craft as developed herein.

II. NONLINEAR XR-3 MODEL HEAVE AND PITCH EQUATIONS

A. BACKGROUND

The original development work on the simplified two-degree-of-freedom model was done by McIntyre [7]. Several weaknesses in the original model were noted by McIntyre in that work.

The major portion of the work presented here was involved in close examination of all aspects of the original model, comparison of the modeling techniques used therin with other methods and remodeling of several important craft physical characteristics.

One major area of investigation was the lack of pitch damping in the original model, which resulted in the addition of an added-mass effect to the pitch moment equations.

Additional changes involve a revision of the force equations for the rear seal, major changes in the way the plenum chamber is modeled (also added to the loads and motion 6-dof model [2]). and a more rigorous development of the planing force equation of [7] .

There are several areas of theory concerning CAB SES modeling where empirical data is lacking due to difficulties with physical measurements. One such area inviting closer inspection was dynamic variation of the

effective center of pressure for the plenum gauge pressure lift effect. A possible approach is suggested herein and included in the model.

B. ASSUMPTIONS

The following assumptions are made for this constant speed, pitch-heave model:

1. Planing forces are concentrated at the centroid of the keel longitudinal cross section.

2. Total seal force is lumped into a pressure differential acting on the seal face area in contact with the water passing beneath the seal.

3. Aerodynamic forces on the forward seal are disregarded.

4. Dynamic variations in moment lever arms are disregarded for all moments except seals and the moment due to plenum guage pressure.

5. Dynamic variations in effective plenum roof area will be included.

6. Any lift effects due to aerodynamic forces are lumped in with the planing forces (for reasons to be developed in Chapt IV.) The moments are included in plenum gauge pressure moments .

7. Constant seal leakage area is assumed.

8. Since this model is for constant surge velocity,

drag and thrust forces are considered to be in equilibrium and in balance for moments about the Y axis.

C. COORDINATE SYSTEM

(see fig. 1)

1. The origin of the cartesian coordinate system is located at the calm-water line, longitudinally and transversly coincident with the craft center of gravity.

2. The X axis is the longitudinal coordinate defined as positive as X increases towards the bow of the craft.

2. The Y axis is the transverse coordinate increasing positively towards the starboard side.

4. The Z axis is the vertical axis, increasing positively in a downward direction.

5. ZS is the vertical distance from the center of gravity to the keel.

6. Z is the vertical distance from the calm water line to the vertical center of gravity.

7. THETA is the pitch angle defined as positive as the bow pitches up.

8. Positive pitch moments are defined as moments which tend to cause a positive increase in the angle THETA.

D. SIDEWALL MODELING

As it was desired to keep all physical dimensions consistant with the six degree of freedom model, scale model drawings were developed with the data from the sidewall subroutine of that model. All sidewall dimensions used in this model were taken from those drawings.

The sidewalls are modeled in two sections, one forward of the longitudinal C.G. and the other aft. Each sidewall is considered to be of constant width at the water line and the keel, with width increasing in the vertical direction according to an average deadrise angle.

The average forward sidewall area is found to be:

(see fig. 2 and 3b)

AVERAGE WIDTH = LDBAR1/(2*TAN(DR1))+WS10

(II-1)

where LDBAR1 is draft at forward centroid, DR1 = average deadrise angle forward and WS10 is the average keel width of the forward section. Therefore submerged volume of a forward sidewall is given by:

VOL = L1*(LDBAR1/(2*TAN(DR1))+WS10)*LDBAR1

(II-2)

where L1 is the length of a forward buoyant section.

Following the same procedures the after sidewall width

is:

(see fig. 2 and 3c)

AVERAGE WIDTH = LDBAR2/(2*TAN(DR2))+WS20

$$(II-3)$$

where DR2 = average deadrise angle aft
LDBAR2 = draft at after buoyant centroid
WS20 = average keel width aft

Submerged volume of an after sidewall is then
determined to be;

VOL = L2*(WS20+LDBAR2/(2*TAN(DR2)))*LDBAR2

$$(II-4)$$

where L2 is the length of the after sidewall.

E. SEAL MODELING

A major change in McIntyre's model was made by
remodeling the stern seal. In the original model a large
negative moment was required to place the pitch
equations in steady state equibibrium. Investigation of
seal forces as presented in [9] revealed a large
discrepancy between the after seal forces generated in
McIntyre's model and calculations based on the
information in [9] . This discrepancy was further
supported by actual seal load data presented by Layton
in [10] . All seal dimensions used in this model were
taken from data presented in [10] . Seal hinge locations
were taken from the data used in [5] .

17

Seal lift force forward is generated by plenum gauge
pressure acting downward on the seal face area in
contact with the water passing underneath the seal.
This downward force results in a lift force being
generated as the downward movement of the seal displaces
the water beneath it.

The seal is considered to have a straight forward face
which runs from the hinge point at the plenum roof to
the bottom of the keel at an angle determined to be
best-fit from the data in ref. [1] . The wetted surface
of the seal is considered to lay parallel to and on the
water at the point where the seal face intercepts the
calm water line. as a result forward seal lift equations
are:

ASEAL1 = WIDTH*XSEAL1

$$(II-5)$$

XSEAL1 = (LD-L3*TAN(THETA))/SIN(31)

$$(II-6)$$

LD = draft at the C.G
L3 = distance from C.G to point of contact for forward
seal face.
LD - L3*TAN(THETA) = draft at forward seal face contact
point
31 degrees is the interior angle of the seal.

The after seal wetted area is determined in a similar
manner to be :

ASEAL2 = WIDTH*XSEAL2

$$(II-7)$$

$$XSEAL2 = (LD+L4*TAN(THETA))/SIN(32)$$

$$(II-8)$$

In this model forward seal pressure is considered equal to plenum pressure. As a result forward seal lift is :

$$HSEALF = PBBAR*ASEAL1$$

$$(II-9)$$

Since plenum guage pressure tends to force the after seal upward, resulting in venting of the plenum air mass, the rear seal is operated at a pressure slightly above that of the plenum to reduce the venting tendency of the after seal. As a result the after seal requires a modification in modeling. In McIntyre's work the pressure differential (PSEAL-PBBAR) only was considered in the lift force. However, as previously stated, there were large discrepancies in computed loads as compared to measured data from [10]. Therefore in this model , the seal working pressure is considered to be PBBAR plus differential pressure. As a result after seal lift is given by:

$$HSEALA = (PBBAR+PDIFF)*ASEAL2$$

$$(II-10)$$

19

F. PLENUM MODELING

In the work presented by McIntyre the plenum was considered a box with the only dynamic dimensional variation being in the Z direction. However (as can be seen in fig. 1), although the forward edge can be assumed to be reasonably constant in the Y-Z plane, the forward face of the rear seal slopes rather steeply. Therefore the plenum length (in the X direction) varies rapidly as draft varies. As a result the effective plenum roof area consists of that area from the after edge of the forward seal to the forward hinge point of the rear seal, plus the vertical projection of the unwetted forward face of the rear seal. As an additional consequence it can be seen that the effective plenum center of pressure varies fore and aft as draft varies . In fact as draft increases the C.P. moves forward.

The following variable names will be used to describe the plenum chamber (see fig. 4.)

LPR = length of plenum roof from the rear edge of the forward seal to the hinge point of the after seal.
LPWL = length of plenum at the keel from the after edge of the forward seals to the transom.
LP = length of plenum at the waterline.
BUBHGT = vertical distance from the plenum roof to the bottom of the keel at the center of gravity.
AB = plenum effective roof area.

Using the previous definitions, the plenum roof length and area is:

LP = LPWL-(LPWL-LPR)*(LD/BUBHGT)

$$(II-11a)$$

and effective plenum roof area is

AB = WIDTH*LP

$$(II-11b)$$

with the result that lift due to plenum gauge pressure is:

HPRES = -AB*PBBAR

$$(II-11c)$$

As a comment on the complexity of the lift forces of this model note that for constant plenum pressure increased draft results in decreased plenum lift.

G. CRAFT DYNAMICS

1. Plenum Air Mass and Pressure Equations

For the purposes of this model the rear seal leakage area is considered constant since to assume otherwise would lead to modeling a very difficult and poorly understood dynamic process. In addition the plenum pressure VS air mass process is assumed to be adiabatic in nature. Fan characteristics are those used in the constant air leakage heave only model of Gerba and Thaler in [14]. Air flow into the plenum is taken as positive.

Therefore the airflow into the chamber is given by:

$$Qin = N*(QIO-Kq*PBBAR)$$

(II-12)

Where N is the number of fans supplying air to the plenum, QIO is the equilibrium air flow rate for the fan with zero gauge pressure and Kq is the slope of the fans' airflow VS gauge pressure curve.

Qout is airflow out of the plenum and is determined by the seal leakage equation:

$$Qout = Cn*Al*(2*PBBAR/RHOA)**1/2$$

(II-13)

Where Cn = seal leakage coefficient, Al = seal leakage area, and RHOA = mass density of air. Therefore mass flow rate is:

$$MBDOT = RHOA*(Qin-Qout)$$

(II-14)

The plenum air dynamics are considered in equilibrium when Qin = Qout

Absolute Plenum Pressure is determined from the adiabatic gas law to be:

$$Pb = Pa*(MB/(RHOA*PBBAR))**GAMMA$$

22

and,

PBBAR = Pb-Pa

Where Pa = ambient atmospheric pressure (LBF/FT**2 GAMMA = adiabatic process coefficient, Pb = plenum absolute pressure, and PBBAR = plenum gauge pressure.

2. Buoyant Forces

Buoyant force is calculated by the submerged volume multiplied by the mass density of the fluid times the gravitational constant.

Therefore forward buoyant force is:

HBF = -2*RHO*G*VOL

Where volume is given by eqn. II-2, RHO is the mass density of water (slugs/ft**3) and G is the gravitational constant. The factor of 2 is introduced to account for 2 sidewalls. The total expression for HBF is:

HBF = -2*RHO*G*L1*LDBAR1*(LDBAR1/(2*TAN(DR1))+WS01)

Following the same pattern,

23

$$HBA = -2*RHO*G*L2*LDBAR2*(LDBAR2/(2*TAN(DR2))=WS10)$$

$$(II-18)$$

3. Seal Forces

Forward seal force is determined from eqn. II-9 to be:

$$HSF = -PBBAR*WIDTH*(LD-L3*TAN(THETA))/SIN(31)$$

$$(II-19)$$

where HSF is the heave force due to forward seal.

In a similar manner HSA is:

$$HSA = (PBBAR+PDIFF)*WIDTH*(LD+L4*TAN(THETA)/SIN(32)$$

$$(II-20)$$

4. Planing Forces

McIntyre introduced the planing force phenomena in his model to account for the proven fact that the CAB SES tends to decrease it's draft and pitch down as speed increases. His development of the planing equation was not well explained and the basis for selection of the planing coefficient was not clearly stated. Reidel [12] did a special investigation of the planing force phenomena. His results were based on flat plate planing effects to approximate the flat bottom of the craft sidewalls.

Since the water is in contact with the vertical portions of the sidewalls it was felt a more accurate representation was neeced. Barnaby [13] states that water contact on the vertical sides of a planing hull rapidly reduces planing lift advantage since one of the advantages of a planing hull is reduced drag due to wetted surface. planing lift results in a speed sensitive tradeoff between static lift (buoyant effects) and dynamic lift (planing effect) that is directly proportional to the angle of attack (for small planing angles) and the square of the velocity. Therefore the planing force is of the form:

HPLAN = K*V**2*THETA

From Reidel's work,

HPLAN = 0.5*AREA*V**2*PI*SIN(THETA)

$$(II-21)$$

for small angle approximations this simplifies to:

HPLAN = RHO*AREA*V**2*PI*THETA

Which is the planing force for a flat plate. Barnaby gives no simple formula for the losses due to immersion so we are left with an arbitrary loss coefficient, PLCOEF such that:

HPLAN = (PLCOEF)*2*RHO*AREA*V**2*PI*THETA

$$(II-22)$$

The added factor of 2 accounts for 2 sidewalls.

The planing area is taken from the scale drawings

25

developed from sidewall data, and the force is assumed
to act at the centroid of the flat keel surface, which
is consistant with Reidel's work. The loss coefficient
will be developed in the section on achieving
equilibrium.

5. Plenum Gauge Pressure Lift

Combining equations II-11a ,II-11b , and II-11c
results in:

HPRES = -PBBAR*WIDTH*(LPWL-(LPWL-LPR)*(LD/BUBHGT))

$$(II-23)$$

6. Total Lift Forces

Lift Total = HPRES + HBF + HBA + HSF + HSA + HPLAN

which must exactly equal craft weight (W) for the hull
to be in vertical equilibrium, or;

W + HPRES + HBF + HBA + HSF + HSA + HPLAN = 0

$$(II-24)$$

defines equilibrium condition in heave motion.

H. CRAFT PITCH MOMENT EQUATIONS

1. Buoyant Moments

Forward buoyant moment is the forward buoyant lift times the effective lever arm, or;

PBF = -HBF*(Lever arm forward)

PBF = -HBF*L5

$$(II-25)$$

Note that the negative sign results from the definition of positive moments and the fact that upward forces are negative by definition.

PBA = HBA*LEVER ARM

PBA = HBA*L6

$$(II-26)$$

using the same reasoning, after buoyant moment is:

PB total = PBF + PBA

$$(II-27)$$

2. Seal Moments

Since the seals are relatively distant from the C.G. dynamic variations in the lever arms are considered in seal moment equations and are developed here.

The seal force is modeled to act at the longitudinal center ofthe seal wetted length. Therefore the effective lever arm for the seal moment is:

$$PLSF = L3 - XSEAL1/2$$

where PLSF = moment lever arm for seal forward. As a result:

$$PSF = -HSF*PLSF$$

$$PSF = -HSF*(L3-(XSEAL1/2))$$

$$(II-28)$$

In a similar manner

$$PLSA = L4 + XSEAL2/2$$

$$PSA = HSA*PLSA$$

$$PSA = HSA*(L4+XSEAL2/2)$$

$$(II-29)$$

$$PS\ TOTAL = PSF+PSA$$

Note that the dynamic pitch sensitivity to moment arm length is included in the XSEAL terms as defined in equations II-6 and II-3.

3. Planing Moment

For the planing force developed in equation II-22 the planing force is concentrated at the centroid of the flat keel which results in:

PPLAN = L7*HPLAN

$$(II-30)$$

4. Plenum Pressure Moment

First the dynamic variation in effective center of pressure will be developed. (see fig.(4))

plenum length is taken from equation II-11a to be

LP = LPWL-(LPWL-LPR)*(LD/BUBHGT)

Defining LDIFF to be

LDIFF = LPWL-LPR

$$(II-31)$$

and,

XCP = XCP0+(LDIFF*LD/BUBHGT)/2

$$(II-32)$$

where

XCP0 = LPWL/2-XCG

$$(II-33)$$

and XCG is the distance from the transom to the C.G.
(see fig. 4 .) Finally,

PPRES = -HPRES*XCP

$$(II-34)$$

5. Pitch Damping Moment

Any frictional damping terms dependent upon the
square of pitch rate (i.e. tangential velocity about the
Y axis) disappear when the Taylor Series expansion is
carried about the zero rate equilibrium point. Since
for small signal approximation the model should reflect
actual craft characteristics, it was hoped that the
changes in seal and plenum modeling would reveal the
missing damping characteristics. As it turned out this
was not the case. Examination of the hydrodynamic
equations in [9] revealed an added mass effect dependant
upon a cross velocity term between linear X direction
velocity U, pitch rate Q, and added-mass at the stern
A33S due to slender body theory applied to the sidewalls
. This moment is:

FP = -A33S*XLSS**2*U*THETADOT

$$(II-35)$$

Where XLSS is the distance from the C.G. to the stern,
and THETADOT is pitch rate.

A33S = YSS**2*RHO*PI/8

$$(II-36)$$

  where YSS is the cross section width of the side wall at the stern waterline. Therefore,

FPDAMP = -2*XLSS**2*A33S*U*THETADOT

   = -2*PI*XLSS**2*YLSS**2*RHO*U*THETDOT /8

$$(II-37)$$

The factor of 2 is introduced to account for two sidewalls.

6. Total Moments

  Since the moments are all referenced to the craft center of gravity, the craft weight contributes zero moment in that frame of reference. Therefore total moments are:

PSF + PSA + PBF + PBA + PRES + PPLAN + PDAMP = 0

$$(II-38)$$

I. HEAVE ACCELERATION EQUATIONS.

  From Newton's law, acceleration and force are related by:

FORCE = MASS*ACCELERATION

For the linearized model we are interested in the acceleration on the craft and as a result:

ACCELERATION = FORCE/ MASS and therefore the heave equation of motion becomes:

ZDDOT = (HBF+HBA+HSA+HPLAN+HPRES)/MASS

(II-39)

where ZDDOT is the second derivative of Z with respect to time.

J. PITCH ACCELERATION EQUATIONS

   Angular acceleration is:

THETADDOT = PTOTAL/IYY

Where IYY is the craft inertial moment about the Y axis. As a result total angular acceleration is;

THETADDOT = (PBF+PBA+PSF+PSA+PPLAN+PPRES+PDAMP)/IYY

(II-40)

   This completes the derivation of all nonlinear equations needed to describe the two-degree-of-freedom CAB SES. In the following chapter these nonlinear equations will be linearized using the Taylor Series expansion about a steady state operating point which will result in the equations needed to generate a

dynamic digital-computer simulation of craft motion in the time-domain.

III. LINEARIZATION OF THE HEAVE-PITCH EQUATIONS.

A. TAYLOR SERIES EXPANSION

For small perturbations about a steady state operating point the nonlinear function Z can be approximated by:

$$Z = Z(X,Y)$$

$$Z(0)+dZ = Z(X(0),Y(0))+(\partial Z/\partial X)*dZ+(\partial Z/\partial Y)*dY$$

where $(\partial Z/\partial X)$ and $(\partial Z/\partial Y)$ are the partial derivatives of the function Z evaluated at the steady state operating point $X(0),Y(0)$. Cancelling the steady state values from both sides of the equation yields the differential model equations:

$$dZ = (\partial Z/\partial X)*dX+(\partial Z/\partial Y)*dY$$

and

$$Z = Z(0)+dZ$$

where dZ,dX, and dY are the differential variables for Z, X, Y respectively, $(\partial Z/\partial X)$ and $(\partial Z/\partial Y)$ are the partial derivatives of Z evaluated at the steady-state operating point.

B. LINEARIZATION OF THE MODEL EQUATIONS

There are basically four equations to linearize for the two-degree-of-freedom model:

ZDDOT = F(Z,THETA,MB)

THETADDOT = G(Z,THETA,THETADOT,MB)

MBDOT = H(Z,MB)

P3BAR = I(Z,MB)

therefore the equations for the differential state variables are:

dZDDOT = (dF/dZ)*dZ+(dF/dTHETA)*dTHETA+(dF/dMB)*dMB

$$(III-1)$$

dTHETADOT = (dG/dZ)*dZ+(dG/dTHETA)*dTHETA+(dG/dMB)*dMB

$$(III-2)$$

dM3DOT = (dH/dZ)*dZ +(dH/dTHETA)*dTHETA+(dH/dMB)*dMB

$$(III-3)$$

$$dPBBAR = (dI/dZ)*dZ+(dI/dTHETA)*dTHETA+(dI/dMB)*dMB$$

$$(III-4)$$

Note that the left hand side variables are differentials, not time derivatives.

C.   LINEARIZED EQUATIONS

1.   Plenum Air Mass Flow Derivatives

$$Qin = N*(Qi0-Kq*PBBAR)$$

$$(II-12)$$

$$Qout = Cn*Al*(2*PBBAR/RHOA)**1/2$$

$$(II-13)$$

$$MBDOT = RHOA*(Qin-Qout)$$

$$(II-14)$$

as a result the differential equation for MBDOT becomes:

$$dMBDOT = RHOA*(dQin-dQout)$$

$$(III-5)$$

$$dQin = (dQin/dZ)*dZ+(dQin/dPBBAR)*dPBBAR+ndQin/dMB)*dMB$$

36

dQin/dPBBAR = -N*Kq

The partial derivatives of Qin with respect to all other variables are zero.

dQout =
(dQout/dZ)*dZ+dQout/dPBBAR)*dPBBAR+(dQout/dMB)*dMB

dQout/dPBBAR = Cn*Al*((RHOA/2*PB3AR)**1/2)/RHOA

(III-7)

The partial derivatives of Qout with respect to all other variables are zero. Inserting equations III-6,and III-7 into II-14 yields the equation for the differential variable dMBDOT:

dMBDOT = (-RHOA*N*Kq-Cn*Al*((RHOA/2*PBBAR)**1/2))*dPBBAR

(II-15)

2. Plenum Gauge Pressure Derivatives.

Pb = Pa*(Mb/RHOA*Vb)**GAMMA

(III-8)

and

PBBAR = Pb-Pa

37

Since Pa is considered constant within the time frame of
this model,

dPBBAR = dPb

<div align="right">(III-9)</div>

As a result,

dPBBAR =
GAMMA*Pa*(MB(0)/RHOA*Vb(0))**(GAMMA-1)*d(MB/RHOA*VB)

where

d(MB/RHOA*VB) = (1/RHOA*VB(0))*dMB+(MB/RHOA)*d(1/VB)

d(MB/RHOA*Vb) = (1/RHOA*VB(0))*dMB-(MB/RHOA*VB**2)*dVB

dVB = d(VN-AB*LD)

dVB = -AB(0)*dLD/dZ-LD(0)*dAB/dZ

remembering that:

LD = Z+ZS

then

dLD/dZ = 1

        we now need the partial of effective plenum roof
area with respect to Z. Defining

AB = ABWL-(ABWL-ABR)*LD/BUBHGT

$$(III-10)$$

ABWL = WIDTH*LPWL

ABR = WIDTH*LPR

further defining

ABDIFF = ABWL-ABR

which is a constant, the effective plenum roof area is:

AB = ABWL-ABDIFF*LD/BUBHGT

using the previous definitions the partial of effective
roof area becomes:

dAB/dZ = -ABDIFF/BUBHGT

$$(III-11)$$

and the differential volume is:

dVb =-(AB(0)-LD(0)*2*(ABDIFF/BUBHGT))*dZ

$$(III-12)$$

with the result that

d(MB/RHOA*Vb) = (1/RHOA*Vb(0))*dZ +

(Mb(0)/RHOA*Vb(0)**2)*(AB(0)-2*LD(0)*(ABDIFF/BUBHGT))*dZ

finally,

$$dPBBAR = GAMMA*Pb(0)*((1/Mb(0))*dMb +$$

$$(1/Vb(0)*(AB(0)-2*LD(0)*(ABDIFF/BUBHGT)))*dZ$$

$$(III-13)$$

3. Heave Force Derivatives

The total heave force equation is:

H(total) = HBF+HBA+HSF+HSA+HPLAN+HPRES

The total partial derivatives will be done term by term.

For the forward buoyant force the following simplifications are made:

HBF = -2*RHO*G*L1*LDBAR1*(LDBAR1/(2*TAN(DR1))+WS10)

let K1 = 2*RHO*G*L1 then,

HBF = -K1*LDBAR1*(LDBAR1/(2*TAN(DR1))+WS10)

where LDBAR1 = (LD-L5TAN(THETA)). Combining the previous two equations,

HBF = -K1*(LD-L5*TAN(THETA))*
    ((LD-L5*TAN(THETA)/(2*TAN(DR1))+WS10)

40

assuming small pitch angles, TAN(THETA) can be approximated by THETA which results in the following simplification:

HBF =
-K1*(LD-L5*THETA)*((LD-L5*THETA)/(2*TAN(DR1))+WS10)

   Taking the partials of HBF with respect to Z and THETA yields:

d(HBF)/dZ = -K1*((LD(0)-L5*THETA(0)/TAN(DR1)+WS10

$$(III-14)$$

and

d(HBF)/dTHETA =
K1*L5*((LD(0)-L5*THETA(0))/(2*TAN(D/r1))+WS10)
   +K1*(-L5/(2*TAN(DR1))*(LD(0)-L5*THETA(0))

Which simplifies to :

d(HBF)/dTHETA =
K1*L5*((LD(0)-L5*THETA(0))/(TAN(DR1))+WS10)

$$(III-15)$$

   Using the same approach, the partials for buoyancy force aft are:

d(HBA)/dZ = -K2*((LD(0)+L6*THETA(0))/(TAN(DR2))+WS20)

$$(III-16)$$

d(HBF)/dTHETA =
-L6*K2*((LD(0)+L6*THETA(0)/(TAN(DR2))+WS10)

$$(III-17)$$

For the forward seal the total differentials are:

DHSF =(d(HSF)/dZ)*dZ+(d(HSF)/dTHETA)*dTHET
    +(d(HSF)/dPBBAR)*dPBBAR

the following simplification is made;

HSF = -PBBAR*WIDTH*(LD-L3*TAN(THETA)/SIN(31)

$$(II-19)$$

let WIDTH/SIN(31) = K3 and TAN(THETA) = THETA, then,

HSF = -K3*PBBAR*(LD-L3*THETA)

with the resultant partials being:

d(HSF)/dZ = -K3*PBBAR(0)

$$(III-18)$$

d(HSF)/dTHETA = K3*L3*PBBAR(0)

$$(III-19)$$

d(HSF)/dPBBAR = -K3*(LD(0)-L3*THETA(0))

$$(III-20)$$

The partials of after seal force are found in the
same manner to be:

dHSA = (d(HSA)/dZ)*dZ+(d(HSA)/dTHETA)*dTHETA
    +(d(HSA/dPBBAR)*dPBBAR

HSA = -(PBBAR+PDIFF)*WIDTH*(LD+L4*TAN(THETA)/SIN(32)

$$(II-20)$$

let K4 = WIDTH/SIN(32) and assume small THETA so that;

HSA = -K4*(PBBAR+PDIFF)*(LD+L4*THETA)

the partials then become:

d(HSA)/dZ = -K4*(PBBAR(0)+PDIFF)

$$(III-21)$$

d(HSA)/dTHETA = -K4*(PBAR(0)+PDIFF)*L4

$$(III-22)$$

d(HSA)/dPBBAR = -K4*(LD(0)+L4*THETA(0))

$$(III-23)$$

    Next the planing force partials are derived:

HPLAN = -2*PLCOEF*RHO*AREA*V**2*PI*THETA

let KPLAN = (2*PLCOEFF*RHO*AREA*PI) then,

43

HPLAN = -KPLAN *V**2*THETA

and,

d(HPLAN) = (d(HPLAN)/dTHETA)*dTHETA

for this constant speed model, therefore,

d(HPLAN)/dTHETA = -KPLAN*V(0)**2

$$(III-24)$$

Plenum Gauge Pressure lift was defined to be:

HPRES = -AB*PBBAR

$$(II-11c)$$

as a result:

d(HPRES)/dPBBAR = -AB(0)

$$(III-25)$$

4. Pitch Moment Partials

The total moments acting on the craft are:

PTOTAL = PBF+PBA+PSF+PSA+PPLAN+PPRES+PDAMP

$$(II-38)$$

The partials of II-38 will be found term by term, beginning with the forward buoyant moment:

44

PBF = -HBF*L5

$$(II-23)$$

therefore:

d(PBF) = -L5*d(HBF)

so that:

d(PBF) = -L5*(d(HBF)/dZ)*dZ-L5*((d(HBF)/dTHETA)*dTHETA

$$(III-26)$$

and the partial of the after buoyant moment is:

PBA = L6*HBA

$$(II-26)$$

dPBA = L6*dHBA

therefore,

d(PBA) = L6*(d(HBA)/dZ)*dZ+L6*(d(HBA)/dTHETA)*dTHETA

$$(III-27)$$

Seal forces partials must include the dynamic
variation in lever arm length, which for the forward
seal is:

PSF = -HSF*PLSF

or,

PSF = (PBBAR *ASEAL1)*PLSF

therefore,

d(PSF)/dPBBAR = ASEAL1(0)*PLSF(0)

(III-28)

and

d(PSF)dZ = PBBAR(0)*d(PLSF*ASEAL1)/dZ

where

d(ASEAL1*PLSF)/dZ = PLSF(0)*d(ASEAL1)/dZ +
    ASEAL1(0)*d(PLSF)/dZ

ASEAL1 = WIDTH*(LD-L3*THETA)/SIN(31)

and

PLSF = L3-(LD-L3*THETA)/2*SIN(31)

therefore,

d(PLSF)/dZ = -1/(2*SIN(31)

and

d(ASEAL1)/dZ = WIDTH/SIN(31)

as a result,

d(PSF)/dZ = PBBAR(0)*((PLSF(0)*WIDTH)/SIN(31) -
    ASEAL1(0)/(2*SIN(31))

46

$$d(psf)/dTHETA = PBAR(0)*d(PLSF*ASEAL1)/dTHETA$$

$$d(PLSF*ASEAL1)/dTHETA =$$
$$PLSF(0)*d(ASEAL1)/dTHETA+ASEAL1(0)*d(PLSF)/dTHETA$$

$$d(ASEAL1)/dTHETA = -L3*WIDTH/SIN(31)$$

$$d(PLSF)/dTHETA = L3/(2*SIN(31)$$

as a result,

$$d(PSF)/dTHETA = -PBBAR(0)*((PLSF(0)*L3*WIDTH)/SIN(31)-$$
$$ASEAL1(0)*L3/(2*SIN(31))$$

For the after seal the derivatives proceed in the manner:

$$PSA = -(PBBAR + PDIFF)*ASEAL2*PLSA$$

$$d(PSA)/dPBBAR = -ASEAL2(0)*PLSA(0)$$

In the same manner as shown in the previous paragraph, the partials of moment due to seals aft with respect to the other variables are:

d(psa)/dZ = -PBBAR(O)*((PLSA(O)*WIDTH)/SIN(32) +

    ASEAL2(0)/(2*SIN(32))

$$(III-32)$$

d(PSA)/dTHETA = -PBAR(0)*((PLSA(0)*L4*WIDTH)/SIN)32) +

   ASEAL2(0)*L4/(2*SIN(32))

$$(III-33)$$

The partial of planing moment is:

PPLAN = L7*HPLAN

$$(II-30)$$

d(PPLAN) = L7*d(HPLAN)

d(PPLAN)/dTHETA = -L7*KPLAN*V(0)**2

$$(III-34)$$

For this constant speed model all other partials are identically zero. The Plenum Gauge Pressure also has dynamic variation in the moment lever arm and the derivatives are:

PPRES = -XCP*HPRES

$$(II-34)$$

therefore,

dPPRES = -HPRES(0)d(XCP)-XCP(0)*d(HPRES)

where

$$XCP = XCP0+(LDIFF*LD)/(2*BUBHGT)$$

therefore,

$$d(XCP)/dZ = LDIFF/(2*BUBHGT)$$

and

$$d(PPRES) = -((HPRES(0)*LDIFF)/(2*BUBHGT))*dZ$$
$$-XCP(0)*d(HPRES)$$

substituting equation (III-25) yields:

$$d(PPRES) = -((HPRES(0)*LDIFF)/(2*BUBHGT))*dZ$$
$$+XCP(0)*AB(0)*dPBBAR$$

Finally, the partial of pitch damping moment is:

$$PDAMP = -2*PI*XLSS**2*YLSS**2*RHO*u*THETADOT/8$$

(II-37)

let

$$2*PI*XLSS**2*YSS**2*RHO/8 = KDAMP$$

then

$$PDAMP = -KDAMP*V*THETADOT$$

as a result, since this is a constant speed model,

49

d(PDAMP)/dTHETDT = -KDAMP*V(0)

$$(III-35)$$

where THETDT is the first derivative of theta with respect to time.

5. Total Differentials

Since F = M * A and the interest is in acceleration terms, A = F/M and dA = d(F)/M. the result being that all differentials must be divided by craft mass to achieve the desired linearized heave results. The same general comment holds true for moment differentials, that is; they all must be divided by the craft moment of inertia about the Y-axis.

All differentials must be sorted by the variable of differentiation so that the linearized differential equations of motion may be written. As an example;

dZDDOT = ((d(HBF)/dZ) +(d(HBA)/dZ))/MASS)*dZ +

The State Variable representation of the system will be presented in a later section of this chapter, however it is convenient to define the State Variables at this time.

$\underline{X}$ = (dZ,dZDOT,dTHETA,dTHETDT,dMB)^t

$$(III-36)$$

and

$\underline{Y} = dPBBAR$

$$(III-37)$$

since PBBAR is not a state variable the definition for dPBBAR must be substituted for dPBBAR in all equations.

6. <u>Total Heave Force Differentials in Z</u>

Here the total differentials will be found. No explanatory text will be included unless special substitutions requiring an aside are necessary.

The buoyancy terms are:

$DHBZ = d(HBF)/dZ + d(HBA)/dZ$

$$(III-38)$$

A term must be included which was not previously derived to account for the sensitivity of seal forces due to PBBAR since it is not a State Variable.

$DHSPZ = (d(HSF)/dPBBAR)*(d(PBBAR)/dZ)$

as a result,

$d(HSF)/dPBBAR = -K3*(LD(0)-L3*THETA(0))$

$$(III-20)$$

and

$DHSFPZ = -K3*(LD(0)-L3*THETA(0))*d(PBBAR)/dZ$

similarly for the after seal moment:

d(HSA)/dPBBAR =-K4*(LD(0)+L4*THETA(0))

$$(III-23)$$

and

DHSAPZ = -K4*(LD(0)+L4*THETA(0))*d(PBBAR)/dZ

The total seal force differential in Z becomes:

DHSZ = d(HSF)/dZ + d(HSA)/dZ +DHSFPZ + DHSAPZ

$$(III-39)$$

For plenum gauge pressure lift differential the same substitution must be made.

dHPRES = -AB(0)*dPBBAR

therefore,

DHPZ = -AB(0)*d(PBBAR)/dZ

$$(III-40)$$

Define the sensitivity coefficient of ZDOT to Z to be:

DZZ = (DHBZ + DHSZ + DHPZ)/MASS

$$(III-41)$$

7. Total Differentials in THETA

52

The following partials are now defined:

DHBTH = d(HBF)/dTHETA + d(HBA)/dTHETA

$$(III-42)$$

DHSTH = d(HSF)/dTHETA + d(HBA)/dTHETA

$$(III-43)$$

DHPTH = d(HPLAN)/dTHETA

$$(III-44)$$

Define the sensitivity coefficient of ZDDOT due to
THETA to be:

DZTH = (DHBTH + DHSTH + DHPTH)/MASS

$$(III-45)$$

8. <u>Total Differentials due to MB</u>

Here since dPBBAR is not a state variable the
partial of PBBAR with respect to MB must be substituted
in the plenum lift and seals lift terms.

d(HSF)/dPBBAR = -K3*(LD(0)-L3*THETA(0))

$$(III-20)$$

by substituting d(PBBAR)/dMB for dPBBAR the result is:

53

d(HSFP)/dMB = -K3*(LD(0)-L3*THETA(0))*d(PBBAR)/dMB

$$(III-46)$$

similarly,

d(HSAP)/dMB = -K4*(LD(0)+L4*THETA(0))*d(PBBAR)/dMB

$$(III-47)$$

d(HPRES) = -AB(0)*dPBBAR

using the previous substitution yields:

d(HPRES)/dMB = -AB(0)*d(PBBAR)/dMB

$$(III-48)$$

The sensitivity coefficient of heave due to MB can now be defined to be:

DZMB = (d(HSFP)/dMB +d(HSAP)/dMB + d(HPRES)/dMB)/MASS

$$(III-49)$$

9. <u>Total Pitch Moment Differentials in Z</u>

DPBZ = d(PBF)/dZ + d(PBA)/dZ

$$(III-50)$$

The dPBBAR substitution yields the partial of seals with respect to pressure with respect to Z.

54

DPSFPZ = ASEAL1(0)*PLSF(0)*d(PBBAR)/dZ

$$(III-51)$$

DPSAPZ = -ASEAL2(0)*PLSA(0)*d(PBBAR)/dZ

$$(III-52)$$

therefore the total seal differential in Z becomes:

DPSZ = DPSFPZ + DPSAPZ +d(PSF)/dZ + d(PSA)/dZ

$$(III-53)$$

Next the Plenum Gauge pressure term is derived:

d(PPRES)/dZ = -HPRES(0)*LDIFF/(2*BUBHGT)

d(PPRES)/dPBBAR = AB(0)*XCP(0)

therefore,

DPPRESZ = AB(0)*XCP(0)*d(PBBAR)/dZ

and

DPRESZ = d(PPRES)/dZ +d(PPRESZ)/dZ

$$(III-54)$$

The sensitivity coefficient of THETA with respect to Z becomes:

DTHZ = (DPBZ + DPSZ + DPPRES)/IYY

$$(III-55)$$

10.   **Total Moment Differentials in THETA**

DPBTH = (d(PBF)/dTHETA + d(PBA)/dTHETA)

$$(III-56)$$

DPSTH = (d(PSF)/dTHETA + d(PSA)/dTHETA

$$(III-57)$$

DPPLTH = d(PPLAN)/dTHETA

$$(III-58)$$

define the sensitivity coefficient for THETA to be:

DTHTH = (DPBTH + DPSTH + DPPLTH)/IYY

$$(III-59)$$

Also, define the sensitivity coefficient in THETDT
to be:

DTHDTH = (d(PDAMP)/dTHDT)/IYY

$$(III-60)$$

11.   **Total Moment Differentials in MB**

dPSAMB = (d(PSA)/dPBBAR) * (d(PBBAR)/dMB)

$$(III-61)$$

dPSFMB =(d(PSF)/dPBBAR) * (d(PBBAR)/dMB)

$$(III-62)$$

DPSMB = DPSAMB + DPSFMB

$$(III-63)$$

Inserting the dPBBAR substitution yields the partial of plenum gauge pressure moment with respect to MB:

d(PPRES)/dPBBAR = -XCP(0)*DHPRES

d(HPRES)/dMB = -AB(0)*d(PBBAR)/dMB

DPPMB = XCP(0)*AB(0)*d(PBBAR)/dMB

$$(III-64)$$

Define the sensitivity coefficient of THETA due to MB to be:

DTHMB = (DPSMB + DPPMB)/IYY

$$(III-65)$$

12. <u>Total Differentials of Air Mass</u>

d(MB)/dMB = (d(MB)/dPBBAR) * (d(PBBAR)/dMB)

define the sensitivity coefficient to be:

DMBMB = d(MB)/dMB

$$\text{(III-66)}$$

define the sensitivity coefficient in Z to be:

DMBZ = d(MB)/dZ

$$\text{(III-67)}$$

D.   TOTAL MODEL SENSITIVITY COEFFICIENTS

   1.   Heave Sensitivity Coefficients

      The sensitivity coefficients for the linearized
differential equation in heave acceleration are:

   DZZ, DZTH, and DZMB.

   2.   Pitch Sensitivity Coefficients

      The sensitivity coefficients for the linearized
differential equation in pitch acceleration are:

   DTHZ, DTHTH, DTHDTH, and DTHMB.

   3.   Plenum Air Mass Sensitivity Coefficients

58

The sensitivity coefficients for plenum air mass are:

DMBZ, and DMBMB.

4. Plenum Gauge Pressure Sensitivity Coefficients

. The sensitivity coefficients for Plenum Gauge Pressure are:

DPBZ, and DPBMB.

E. STATE SPACE REPRESENTATION

The state matrix form of a dynamic system is:

$\underline{XDOT} = A\underline{X} + B\underline{U}$

where $\underline{X}$ = a vector of variables representing the states of a set of first order linear differential equations, and $\underline{U}$ is the vector of forcing functions, and A and B are the matrices of the respective gains. The form of the equations is:

X1DOT = X2

X2DOT = X3

X3DOT = K1*X1 + K2*X2 + K3*X3

for the linearized model of the CAB SES the state
variables were defined to be :

$$\underline{X} = (dZ,\ dZDOT,\ dTHETA,\ dTHETDT,\ dMB)^t$$

As a result the state matrix representation of the
linearized unforced Heave-Pitch model is:

$$
\begin{bmatrix} X1DOT \\ X2DOT \\ X3DOT \\ X4DOT \\ X5DOT \end{bmatrix}
=
\begin{bmatrix}
0 & 1 & 0 & 0 & 0 \\
DZZ & 0 & DZTH & 0 & DZMB \\
0 & 0 & 0 & 1 & 0 \\
DTHZ & 0 & DTHTH & DTHDTH & DTHMB \\
DMBZ & 0 & 0 & 0 & DMBMB
\end{bmatrix}
\begin{bmatrix} X1 \\ X2 \\ X3 \\ X4 \\ X5 \end{bmatrix}
$$

(III-68)

and

$$dPBBAR = DPBZ*X1 + DPBMB*X5$$

III-69

IV.   TIME DOMAIN VALIDATION

The linearized model developed in chapter III was
validated against the the Six-degree-of-freedom
nonlinear model. There were several changes made in the
simulation techniques used, and at the same time the
changes in center of pressure dynamic variation and
planing forces were entered into the 6 DOF model.
Establishment of equibibrium for the linear model was
accomplished off-line using a TI-59 programmable
hand-held calculator with printer.

The first change in simulation technique is the
operating point at which the linear sensitivity
coefficients were evaluated. In McIntyre's model these
coefficients were evaluated at the initial operating
point. In this work the coefficients are evaluated at
the final steady-state equilibrium point since this is
customary in linearization work.

The second major change in simulation was the method
used to determine the planing force loss coefficient
(PLCOEFF) and the establishment of the arbitrary
location of the initial plenum center of pressure. In
this model all heave forces are well defined (as modeled
here) with the exception of planing force lift. As a
result, craft weight and all heave forces except that
due to planing lift are summed and the residual assumed
to be due to the planing phemonema. This residual is
then used to determine (off-line) the value of PLCOEFF.
Note that this method also accounts for any lift due to
aerodynamic forces on the bow that were disregarded.

61

Next all moments are summed about the C.G. except the moment due to plenum pressure lift. The residual moment is assumed to be due to plenum pressure. This residual is used (again off-line) to establish the initial center of pressure. This accounts for any moments not previously accounted for (such as aerodynamic forces on the bow.) McIntyre used the planing lift coefficient to force the model into agreement with the 6 DOF model for natural pitch frequency and used a large, arbitrary, and static moment to force the models into steady state pitch angle agreement. It was felt that using the present method of determination would leave the equations in a form that would be more amenable to extraction of the factors most directly affecting craft characteristics as modeled herein.

A. LINEAR PROGRAM DESCRIPTION

User's instructions have been included as appendix A. The program flow can be isolated into four main sections.

1. First the values for craft weight, draft, pitch angle, plenum pressure and speed are entered. To initialize plenum air mass, draft is used to solve for initial plenum air volume, which is then used with initial plenum gauge pressure to solve equation II-15 for plenum air mass. Equation II-12 is then solved for Qin. Qout is set equal to Qin and equation II-13 is solved for seal leakage area. All other heave and pitch nonlinear equations are solved and their values are listed along with residuals of heave and pitch summations. These residuals are added to the initial values of C.G. and angular acceleration and the initial

values are saved for the time domain simulation section.

2. The same operations are carried out for the steady state values of weight, draft, pitch angle, and plenum pressure. The residuals, forces and moments are again listed.

3. These steady state values are used to evaluate the sensitivity coefficients developed in chapter III which are also listed.

4. Finally the state variable solution is simulated using a four-point fixed step Runge-Kutta algorithm and listed for the print interval desired. The option is included to output either printer plot graphical display using the NPS printer plot subroutine PLOTP or the X-Y Versatec plot subroutine DRAWP. The latter should be used for final runs only, with PLOTP used on intermediate runs. Provisions are made for up to 300 discrete output points for the time domain tabular listing.

B. SIX-DEGREE-OF-FREEDOM MODEL SOLUTION

Two changes were made in the 6 DOF model to account in a more analytic manner for the observed tendency of the XR-3 to pitch down as speed increased.

The first change was to remove an empirical equation used to correct the center of pressure [5] and replace it with the dynamic center of pressure variation developed in chapter II.

The second change was to include in the sidewall subroutine the nonlinear equation for planing forces, with the loss coefficient adjusted to make up (as

63

closely as possible) for lift loss due to the revised modeling of the plenum chamber.

Finally, the 6 DOF model was ran at both 6722 lbs and 6050 lbs weight to establish the initial and final operating points, followed by the weight removal transient run for time domain validation of the linear heave-pitch model.

It should be noted that further study of the 6 DOF model is needed to evaluate the results of the two changes and to more closely establish the arbitrary initial location of the center of pressure. The large amount of CPU and turn-around program times required to run the nonlinear model precluded including that study in this work. Also, for the nonlinear model, X-direction thrust was held constant during the run with the result that speed was 30.38 knots and still increasing at the end of the five second run. This effect will be further discussed in the next section.

C. COMPARISON OF RESULTS

The graphical output for the five second runs are shown in figures 5 through 8 for the linear model and figures 9 through 12 for the nonlinear model. The fixed integration step size was 0.005 sec for the linear model and 0.001 sec for the nonlinear model.

1. Plenum Gauge Pressure Transient

(see fig. 5 and 9)

In general both models exhibited a rapid initial reduction in pressure followed by a smooth transient back towards the final operating pressure. For the linear model the minimum occured at 100 milli-seconds, and 110 milli-seconds for the 6 DOF model, with the respective pressures being 21.38 and 21.30. The final values were 24.31 and 24.08 for the linear and nonlinear model respectively.

As can be seen from the graphical data excellent agreement was acheived between the two models.

2. Draft Transient

(see fig. 6 and 10)

Both models exhibit a smooth exponential type transient towards the final, lower steady-state draft. The linear model transient settles towards a lower value (6.04 inches as compared to 6.44) which is in part attributed to a difference in modeling of the seal forces. The nonlinear model uses a complex combination of hydrodynamic and hydrostatic lift where the linear model uses a simple pressure differential effect. Also, since the nonlinear model is settling to a significantly lower pitch angle (see para. 4 below), the planing force effect is reduced in that model.

3. C.G Acceleration

(see fig. 7 and 11)

Both models show a rapid positive transient in acceleration that closely follows the negative transient

65

in plenum pressure. Both models reached the initial peak positive C.G. acceleration at approximately 20 milli-seconds after the plenum pressure completed the negative transient. The linear model appears to have greater coupling between pitch and heave looking at the C.G. acceleration, but this is not actually supportable since the linear model has greater pitch amplitude excursions about the exponential pitch transient to the lower steady state value (see fig. 8 and 12.) In general the two models show excellent agreement in transient and damped C.G. acceleration behavior.

4. Pitch Transient

(see fig. 8 and 12)

It is in this area that the two models are in greatest disagreement. Both exhibit a general damped sinusoidal behavior about a center exponential transient to a lower steady state value. In both cases the initial excursion is downward. The natural pitch fequency of linear model is approximately 4.8 radians per second, whereas the nonlinear model exhibits a natural pitch frequency of 6.98 radians per second. There is felt to be one major factor contributing to this large discrepancy, which is the inclusion of the planing force in the nonlinear model. Data presented by Thaler and Gerba [14] showed a natural pitch frequency of 5.8 radians per second and much higher oscillations about the exponential transient. It is felt that the simplified planing forces of the linear model are included in the much more complex hydrodynamic equations of the nonlinear model and are therefore redundant in that model. Due to time constraints, that avenue of investigation is left for future studies. The linear

model is tending towards a steady state value on the order of 0.45 degrees whereas the nonlinear model is tending towards approximately 0.30 degrees. This large discrepancy is partially due to the redundant planing force in the nonlinear model and the fact that speed is also increasing in the nonlinear model which tends to accentuate the planing force and force the craft to pitch down.

In the next chapter a signal flow graph will be developed and Mason's Gain Rule applied to explain the linear model characteristic response in a more analytical fashion.

V. SIGNAL FLOW GRAPH AND MASON'S GAIN RULE

A. INTRODUCTION

The State Variables defined in Chapt II are used to develop a signal flow graph of the craft heave-pitch dynamics. Mason's Gain rule is applied to the signal flow graph to derive analytical S-domain polynomials expressing the transfer functions for pitch moment into pitch angle, heave acceleration into draft and the two cross gains. Using typical gains calculated in the time domain program developed in Chapt III the roots of these polynomials are located and it is shown that pitch dynamics may be very closely approximated by a second-order system. Heave dynamics are also simplified.

Using a simplified approach to the frequency response of the craft to non calm-water conditions, the basics are developed for later sea-state model work. A dynamic system modeling program available at the Naval Postgraduate School is used to generate Bode plots for the craft's frequency response in Heave and Pitch under the simplifying assumptions.

B. SIGNAL FLOW GRAPH ANALYSIS

Fig 13 was generated using the sensitivity

coefficients defined in Chapter III. From that graph the following feed-forward and feedback loops and paths were identified:

1. Feed Forward, U(THETA) into THETA.

$$P1 = (1/IYY)*(1/S**2)$$

2. Feed Forward, U(Z) into Z.

$$P2 = (1/MASS)*(1/S**2)$$

3. Feed Forward, U(THETA) into Z.

$$P3 = (1/IYY)*DZTH*(1/S**4)$$

4. Feed Forward, U(Z) into THETA.

$$P4 = (1/MASS)*DTHZ*(1/S**4)$$

5. Feedback Loops.

$$L1 = DTHTH/S**2$$

$$L2 = DTHDTH/S$$

$$L3 = (DZTH)*(DTHZ)/S**4$$

$$L4 = (DZMB)*(DMBZ)/S**3$$

L5 = DZZ/S**2

L6 = DMBMB/S

L7 = (DZTH)*(DMBZ)*(DTHMB)/S**5

C. MASON'S GAIN RULE APPLIED

   Mason's gain rule for a closed multi-loop system is:

T = SUM(Pk*DELTAk)/DELTA

where,
   T = transmission gain from an input to an output
node.
   DELTA = the graph determinant
   DELTAk = cofactor of the kth path
   Pk = gain of the direct path from input to output

   Using Mason's gain rule the graph determinant (DELTA)
is found to be of the form:

D(s) = (B5*S**5 + B4*s**4 + B3*s**3 + B2*s**2 + B1*s +
B0)/S**5

The forward direct path U(THETA) to THETA is:

N1(s) = (1/IYY)*(1/S**5)*(A3*s**3 + A2*s**2 + A1*S + A0)

   The forward path U(Z) to Z was found to be:

70

N2(s) = (1/MASS)*(1/S**5)*(A3*s**3 + A2*s**2 + A1*s + A0)

   The forward direct path U(THETA) to Z is:

N3(S) = (1/IYY)*DZTH*(S + A0)/S**4

   The forward path for draft coupling into pitch (U(Z) to THETA is:

N4 = (1/MASS)*DTHZ*(S + A0)/S**4

D. SOLUTION OF THE INDIVIDUAL POLYNOMIALS

   The gains used below were taken from a typical time domain run as developed in chapter IV.

      DZZ = -2178.0
      DZTH = -121.3
      DZMB = -5499.0
      DTHZ = 28.78
      DTHTH = -22.31
      DTHMB = 72.1
      DMBZ = -28.79
      DMBMB = -73.11

1. Solution of the Graph Determinant

         Inserting the numerical values for the typical sensitivity coefficients listed above and using only the

dominant terms where possible, the roots of the graph
determinant were found to be:

DELTA = (S**2 + 71.8*S + 2066)*(S + 0.5086)*(S**2 +
0.72*S +22.74)/S**5

These factors represent a pair of complex poles
located at -35.71± j27.84 , a real pole located at
-0.5085 , a pair of complex conjugate roots located at
-0.360 ± j 4.755 , and a fifth order zero located at the
origin.

2. Solution of N1(S)

N1(S) = (1/IYY)*(S + 0.427)*(S**2 + 72.68*S + 2146)/S**5

This polynomial factors into a real zero located
at -0.427 , a pair of complex conjugate zeros located at
-36.34 ± j 28.74 , and a fifth order pole located at the
origin.

3. Solution of N2(S)

N2(S) = (1/MASS)*(S**2 + 0.7721*S + 22.35)*(S +
72.38)/S**5

Which factors into a pair of complex conjugate
zeros located at -0.3856 ± j 4.712 , a real zero at
-72.38 , and a fifth order pole located at the origin.

4. Solution of N3(S)

N3(S) = (1/IYY)*DZTH*(S + 73.11)/S**4

   Which represents a real zero   at -73.11,   and   a
fourth order pole at the origin.

   5. Solution of N4(S)

N4(S) = (1/MASS)*DTHZ*(S + 73.11)/S**4

   Which has the same pole and zero locations as
N3(S).

E. SIMPLIFICATION OF TRANSFER FUNCTIONS

   1. T1(S)

T1(S) = THETA(S)/U(THETA,S)

   Therefore from Mason's Gain Rule:

T1(S) = N1(S)/DELTA

T1(S) = (1/IYY)*(S + 35.34 $\pm$ 428.7)*(S + 0.427)/
   (S + 35.1 $\pm$ j 27.84)*(S + 0.508)*(S + 0.36 $\pm$ j 4.755)

To simplify let the complex conjugate zeros at
−36.34 ± j28.7 cancel the poles at −35.9 ± j27.84 , and
the real zero at −0.427 cancell the pole at −0.508.
The result is the simplified second order system:

T1(S) = (1/IYY)/(S**2 + 0.72*s + 22.74)

Inspection of the time domain pitch response with
respect to natural frequeny and damping confirms this
basic underdamped second order response.

2. T2(S)

T2(S) = Z(S)/U(Z,S)

T2(S) = (1/MASS)*(S + 0.3856 ± j4.712)*(S + 72.38)/
    (S**2 +35.1 ± j 27.84)*(s + 0.5085)*((S +0.35 ±
j4.755)

Canceling the pole at −0.36 ± j 4.755 with the
zero at −0.3856 ± j4.712 results in the simplified
response:

T2(S) = (1/MASS)*(S + 72.33)/(S + 0.508)*(S**2 + 71.8*S
+ 2066)

Further simplification can be made if (S +
72.33)/(S + 0.508) is approximated by 72.33/(S + 0.508)
(which is valid for longer time period considerations.)
As a result T2(S) becomes:

74

T2(S) = (72.33/MASS)/(S+0.508)*(S**2 + 71.8*S + 2066)

which has poles located at -0.508, and -35.9± j27.83
This is in quite close agreement with the results
obtained by Thaler and Gerba 14 for the same airflow
condition (Kq = 1.0) for their heave-only linearized
model. Their results were a real pole at -0.33 and a
complex pair at -35.1± j34.4 . This is of the form:

T(S) = K/(S + 0.38)*(S**2 + 70.2*S + 2415)

  3. T3(S)

      Here it is noted that there are no pole zero pairs
that conveniently cancel so that the transfer function
becomes:

T3(S) = (1/IYY)*DZTH*S*(S + 72.33)/
   (S + 35.1 ± j 27.84)*(s+ 0.5085)*(S + 0.36 ± j4.775)

      Making the simplification used in the previous
section, the result is:

T3(S) = (72.33/IYY)*DZTH*S/(s**2 + 71.8*S + 2066)*
   (S + 0.508)*(S**2 + 0.72*S + 22.74)

      Which can be further simplified by looking at the
long term response vice initial few milli-seconds to
(S/(S + 0.508)) = 2 so that:

T3(S) = (142/IYY)*DZTH/(s**2 + 71.8*s + 2066)*(s**2 + 0.72*s + 22.74)

4. <u>T4(S)</u>

Since the transfer fundtions are the same except for the gains the solutions are the same except for the gains:

T4(S) = (1/MASS)*DTHZ * S*(S + 72.33)/DELTA

where the same simplifying assumptions may be applied.

F. SIMPLIFIED BODE PLOT ANALYSIS

1. <u>Simplifying Assumption</u>

(see fig. 12)

The assumption is made that the craft linearized frequency response transfer functions can be separated into two transfer functions.

The first block G1(W,U,...) expresses the disturbing moments and accelerations generated by the craft interacting with the waves. This function was developed by Thaler and Gerba [14] for the heave-only model. In that simpler model the function G1 was a complex function of encounter frequency, angle of incidence, craft length compared to encounter wavelength etc.. This portion of the overall frequency response of this model is left for future work due to time

76

constraints.

The second block G2(We) represents the heave-pitch dynamics of the model as developed in chapters II, III, and IV, which respond to the disturbing moments and accelerations from block G1.

The Transfer functions T1 and T2 (unsimplified) were simulated using the IBM-360 simulation language DSL with S = jW with the following results.

2.   Bode Plots for Pitch Dynamics

(see figs.   15   and   16)

Figure 15 represents the normalized (numerator gain constants set to 1) gain in dB's versus Omega. Note that the abscissa scale is Omega in powers of 10 since this is a convenient means to achieve a logarithmic scale on the X-Y plotter output. As can be seen the response strongly supports the simplification to second-order system. These plots represent the full transfer function T1(jW) vice the simplified system. Figure 16 further supports the simplification as the phase plot starts at zero degrees and shows only a very slight positive increase prior to the rapid change toward -180 characteristic of an underdamped system. Also note that above the damped natural frequency the magnitude plot falls at -12 dB per octave.

3.   Bode Plots for Heave Dynamics

(see figs.   17 and 18)

Figure 17 represents the normalized magnitude versus Omega for the heave dynamics. The system is characteristic of an overdamped third order system with small gain increases at the craft's natural pitch frequency, which represents the pitch dynamics feeding back into heave dynamics. However the gain magnitude curve has already fallen 20 dB below it's lower frequency response gain before the pitch coupling begins to manifest itself. As can be seen in fig. 18 the phase plot shows the same third order pole response with slight second order zero influence at the natural pitch frequency.

VI. CONCLUSIONS AND RECOMMENDATIONS

As shown in Chapters IV and V the simplified Pitch-Heave model developed herein is a very reasonable simulation of the XR-3 test craft for the given operating conditions. Heave, Pressure, and C.G. Acceleration were in very close agreement. Pitch on the other hand showed some difference in natural frequency and damping factor. It is felt that this difference is primarily attributable to the inclusion of a redundant planing force calculation in the 6 DOF model. Historically the results of the 6 DOF computations 14 for pitch response have been very similar to the results for the linear model, in both natural frequency and damping characteristics. This can be attributed to the fact that the additional planing force did not exist in the original 6 DOF program.

Since one of the major concerns with the 6 DOF model is the excessive computational times involved in sea-state simulations the conclusion may be drawn that eventual substitution of the sidewall and seal force linear model equation in the 6 DOF program will substantially reduce CPU time, with some resultant loss in computational accuracy. By way of comparison, disregarding compiling time and output time, the linear model required approximately 9 seconds of CPU time for the 5 second simulation while the 6 DOF model required 9 minutes of CPU for the 5 second run. This is a computation time improvement on the order of 60 times.

From the time-domain plenum gauge pressure data it can

be seen that the dynamic variation in effective plenum roof area has a noticeable effect on the plenum pressure transient behavior as compared to previous results 14 . The initial pressure down transient was faster, dropped to a lower value , and began it's recovery more quickly. Therefore the plenum roof dynamic variations strongly affects the C.G. acceleration characteristics of the craft and therefore it's transient behavior.

The dynamic center of pressure variation developed herein proved to be a very draft sensitive phenomenon. Although the length of the other lever arms as modeled herein change by a similar amount, percentage of variation is radically different. For the seals the variation is on the order of inches in 10 feet, where the variation in lever arm for plenum pressure lift is on the order of inches in a single foot (or less.) This implies that dynamic C.P. variation is the dominant factor in steady state pitch angle versus steady state draft.

Planing forces as included in this model are now in a form where the basic factors as far as craft construction characteristics are readily recognized. This force provides part of the answer to craft pitch-down characteristics as initially investigated by Reidel [9] , with the remainder of the moment being developed by the C.P. variation for pressure. The planing force provides a clue as to how, during construction, the craft's pitch amplitude excursion characteristics may be controlled.

Several areas for future investigation have become apparent in this work.

1. Verification of the effect of dynamic center of

pressure variation and planing forces as incorporated in the 6 DOF model over the entire speed operating range.

2. Incorporate the simple modeling for sidewalls and seals into the 6 DOF model and investigate the trade-off between CPU time and computational accuracy.

3. A closer look at the seal forces used herein. It is possible that a simple gain factor needs to be included in these equations in order to optimize the steady-state seal forces with respect to actual load data as measured during experimental test runs of the craft 10 .

4. Incorporate sea state forces and moments into the simplified model by simulation of the forces and moments that are generated by craft interaction with the sea. Evaluate the accuracy of the method used by comparison with data generated by the simple model and the 6 DOF model in sea-state conditions.

5. Analytical investigation of the craft physical characteristics that have predominant influence on the natural pitch frequency and damping by using the gain terms from the results of the signal flow graph analysis done in Chapter V.

6. Use the simplified model to develop a ride-comfort control system. Test the resulting design on the 6 DOF model, and compare the results obtained with those suggested by ROHR [7]. It has been known empirically for some time that the craft exhibited simple second order behavior in the pitch mode. Now that this fact has been analytically verified the implications for an automatic control system for pitch response are powerful. A simple control system can be visualized

that does not involve either complex optimal control
system design work or hardware. A simple acceleration
and rate feedback control system is implied, with the
possibility of adding a speed input to the system to
compensate for the localized linearity of the craft
characteristics.

APPENDIX A

LINEAR SES MODEL USER'S GUIDE

A. General Comments

The program as listed following Appendix B is intended for useage via the hot card reader at NPS.

It is intended to run in Fortran G with Plotting option (PROC = FORTCLGP.)

The program is structured on the assumption that the initial and final state variables are in equilibrium prior to data entry, but will run regardless. The force and moment residual listings will indicate the value of imbalance, if any.

The craft physical dimensions are alterable by changing the cards in the craft dimension section of the main program, which are keyed to the craft geometry herein.

B. Data Deck Setup.

The /* and //GO.SYSIN DD * cards are inserted following the end card in Subroutine VERSAP, followed by the data deck as described

1. Plot option card (IPLOT), format I1. IPLOT = 1 = VERSATEC X-Y plotter output.

   IPLOT = 0 = PRT PLOT output

2. List option card (ILIST), Format I1

ILIST = 1 = Forces and moments, with residuals and all
sensitivity coefficients listed.

ILIST = 0 = Input craft operating conditions only
listed.

3. Time and Integration variables.

TI, TF, NPTS, NSTEP Format (2F10.4,2I10)

Ti = problem start time (normally 0.0)

TF = Problem stop time (seconds)

NPTS = number of tabular output points desired.

NSTEP = number of integration steps.

note: it is best to make NSTEP an integer multiple
of NPTS, and never less than NPTS.

4.Planing coefficient and arbitrary center of pressure
input, i.e. READ( ) AKP, PLCOEFF

Format = 2F10.4

5. Initial Conditions card.

The initial craft conditions are read in in the
following order: weight(Lbs.), Draft (in), Pitch angle
(Deg.)), PBBAR (psf), and speed(fps.) Format is 5F10.4

6. Final Conditions.

The final conditions are read in the following order
and format: weight (Lbs), Draft (in), Pitch angle
(Deg), and PBBAR(psf), Format 4F10.4. Since this is a
constant speed model, initial and final speed are
assumed equal.

7. Label Cards.

Label cards for VERSATEC output are the last 10 cards.

There are five graphs in this mode. Draft(in), C.G. Acceleration (G's), Pitch Angle (Deg.), Pitch Acceleration (Deg/SEC**2), and PBBAR (Each graph requires two label cards, Format (6A8), which print on two lines below the graph. The graphs are output in the order listed above.

APPENDIX B

DRAWINGS AND FIGURES

Figure 1 - ASSUMED GEOMETRY

87

Figure 2 - ASSUMED GEOMETRY (CONT)

BOW SEAL
(Details of Stern Seal the same)

FIGURE 3A

VERTICAL CROSS SECTION
FORWARD

FIGURE 3B

VERTICAL CROSS SECTION
AFT

FIGURE 3C

Figure 3 - ASSUMED GEOMETRY (CONT)

Figure 4 - PLENUM CHAMBER MODELING

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=5.00E+00 UNITS INCH.
PLØT IS PLENUM GAUGE PRESS
CAB SES LINEAR 2 DØF MØDEL
Figure   5 -   LINEAR PLENUM PRESSURE TRANSIENT

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=2.00E+00 UNITS INCH.
  PLOT IS DRAFT (INCHES)
  CAB SES LINEAR 2 DOF MODEL
      Figure 6 - LINEAR DRAFT TRANSIENT

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=2.00E-02 UNITS INCH.
PLOT IS CG ACCEL (GEES)
CAB SES LINEAR 2 DOF MODEL

Figure   7 -   LINEAR C.G. ACCELERATION

93

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=1.00E-01 UNITS INCH.
PLOT IS PITCH ANGLE
CAB SES LINEAR 2 DOF MODEL
Figure   8 -   LINEAR PITCH TRANSIENT

94

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=5.00E+00 UNITS INCH.
 30 KNØT RUN
PLØT IS PLENUM PRESSURE
          Figure   9 -   6 DOF PLENUM PRESSURE TRANSIENT

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=2.00E+00 UNITS INCH.
  30 KNØT RUN
PLØT IS Z DISPLACEMENT
        Figure 10 - 6 DOF DRAFT TRANSIENT

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=2.00E-02 UNITS INCH.
  30 KNOT RUN
PLOT IS C.G.ACCELERATION
        Figure 11 - 6 DOF C.G. ACCELERATION

X-SCALE=1.00E+00 UNITS INCH.
Y-SCALE=1.00E-01 UNITS INCH.
30 KNOT RUN
PLOT IS PITCH ANGLE

Figure 12 - 6 DOF PITCH TRANSIENT

Figure 13 - SIGNAL FLOW GRAPH

99

Figure 14 - HEAVE PITCH TRANSFER FUNCTION

XSCALE= 0.80   UNITS/INCH RUN NO. 1
YSCALE= 10.00   UNITS/INCH PLOT NO. 1

Figure 15 - LINEAR PITCH BODE PLOT (MAG)

XSCALE= 0.80   UNITS/INCH   RUN   NO. 1
YSCALE= 40.00   UNITS/INCH   PLOT NO. 2

Figure 16 -   LINEAR PITCH BODE PLOT (PHASE)

XSCALE= 0.80   UNITS/INCH RUN NO. 1
YSCALE= 8.00   UNITS/INCH PLOT NO. 1

Figure 17 - LINEAR HEAVE BODE PLOT (MAG)

XSCALE= 0.80   UNITS/INCH RUN NO. 1
YSCALE= 40.00   UNITS/INCH PLOT NO. 2

Figure   18 -   LINEAR HEAVE BODE PLOT (PHASE)

```
      DIMENSION OUTVEC(300,6),PLOTV(300),TIME(300),QPOINT(6)      SES00010
      DIMENSION ZI(2),THETAI(2),AMBI(2),PBBARI(2)                 SES00020
      COMMON/INTEG/X(6),XDOT(6),T,H,NPASS                         SES00030
     1COMMON/DERIV/DZZ,DZPH,DZMB,DZFH,DTHZ,DTHPH,DTHMB,DTHFH,DTHDTH,DMBMB,DMBZ, SES00040
     1DPHDZ,DPBMB,ACCEL,PACCEL                                    SES00050
      DATA OUTVEC,PLOTV,TIME/1800*0.0,300*0.0,300*0.0/            SES00060
      WRITE(6,9606)                                               SES00070
      WRITE(6,9605)                                               SES00080
C                                                                 SES00090
C     PHYSICAL CONSTANTS                                          SES00100
C                                                                 SES00110
      G=32.2                                                      SES00120
      GAMMA=1.4                                                   SES00130
      PA=2116.0                                                   SES00140
      PI=3.141593                                                 SES00150
      RHO=2.0                                                     SES00160
      RHOA=0.002378                                               SES00170
C                                                                 SES00180
C     CRAFT DIMENSIONS                                            SES00190
C                                                                 SES00200
      WIDTH=10.0                                                  SES00210
      AL1=10.3                                                    SES00220
      AL2=9.6                                                     SES00230
      AL3=11.2                                                    SES00240
      AL4=8.26                                                    SES00250
      AL5=AL1/2.0                                                 SES00260
      AL6=AL2/2.0                                                 SES00270
      AL7=4.227                                                   SES00280
      AL8=17.1                                                    SES00290
      DR1=61.0                                                    SES00300
      DR2=68.5                                                    SES00310
      WS10=0.2                                                    SES00320
      WS20=0.52                                                   SES00330
      CN=0.9                                                      SES00340
      ALPR=15.72                                                  SES00350
      ALPWL=19.65                                                 SES00360
      ALDIFF=ALPWL-ALPR                                           SES00370
      ABDIFF=ALDIFF*WIDTH                                         SES00380
      XCPO=ALPWL/2.0-(119.6/12.0)                                 SES00390
      ABW=ALPWL*WIDTH                                             SES00400
      ABR=ALPR*WIDTH                                              SES00410
      BUBHGT=1.915                                                SES00420
      VN=(ALPR+ALPWL)/2.0)*BUBHGT*WIDTH                           SES00430
      ZS=2.5                                                      SES00440
      QIO=35.0                                                    SES00450
      EN=5.00                                                     SES00460
      A33S=0.7088                                                 SES00470
      AIYY=9320                                                   SES00490
```

105

```fortran
C
C     ANGULAR CONVERSION FACTORS AND CONVERSIONS
C
      RADEG=360.0/(2.0*PI)                                              SES00500
      DEGRAD=(2.0*PI)/360.0                                            SES00510
      DR1=DR1*DEGRAD                                                   SES00520
      DR2=DR2*DEGRAD                                                   SES00530
      NORD=6                                                           SES00540
      DO 01 I=1,NORD                                                   SES00550
      XDOT(I)=0.0                                                      SES00560
      X(I)=0.0                                                         SES00570
      QPOINT(I)=0.0                                                    SES00580
   01 CONTINUE                                                         SES00590
      READ(5,9501) IPLOT                                               SES00600
 9501 FORMAT(I1)                                                       SES00610
C                                                                      SES00620
C     INPUT PROBLEM PARAMETERS
C
      READ(5,9502) ILIST                                               SES00630
 9502 FORMAT(I1)                                                       SES00640
      READ(5,9500) TI,TF,NPTS,NSTEP                                    SES00650
      WRITE(6,9610) TI,TF,NPTS,NSTEP                                   SES00660
      READ(5,9503) AKP,XCPC                                            SES00670
 9503 FORMAT(2F10.4)                                                   SES00680
C                                                                      SES00690
C     INPUT INITIAL OPERATING POINT                                    SES00700
C
      READ(5,9505) W,ALD,THETA,PBBAR,V                                 SES00710
      WRITE(6,9615) W,ALD,THETA,PBBAR,V                                SES00720
C                                                                      SES00730
C     CALCULATE INTERMEDIATE VARIABLES AND CONVERSIONS                 SES00740
C                                                                      SES00750
      I=0                                                              SES00760
      J=1                                                              SES00770
      AMASS=W/G                                                        SES00780
      ALD=ALD/12.0                                                     SES00790
    5 THETA=THETA*DEGRAD                                               SES00800
      AKDMP=2.0*AL2*AL2*A33S                                           SES00810
      ALD1=ALD-AL5*THETA                                               SES00820
      ALD2=ALD+AL6*THETA                                               SES00830
      WS1=WS10+(ALD1/(2.0*TAN(DR1)))                                   SES00840
      WS2=WS20+(ALD2/(2.0*TAN(DR2)))                                   SES00850
      AK1=2.0*RHO*G*AL1                                                SES00860
      AK2=2.0*RHO*G*AL2                                                SES00870
      AK3=WIDTH/(SIN(31*DEGRAD))                                       SES00880
      AK4=WIDTH/(SIN(32*DEGRAD))                                       SES00890
      XSEAL1=(ALD-AL3*THETA)/SIN(31.0*DEGRAD)                          SES00900
      XSEAL2=(ALD+AL4*THETA)/SIN(32.0*DEGRAD)                          SES00910
```

```
      ASEAL1=WIDTH*XSEAL1                                              SES00950
      ASEAL2=WIDTH*XSEAL2                                              SES00960
      WSPL1=WS10*AL1                                                   SES00970
      WSPL2=WS20*AL2                                                   SES00980
      XCP=XCPO+(ALDIFF*ALD/BUBHGT)/2.0+XCPC                            SES00990
      AB=ABW-(ABW-ABR)*(ALD/BUBHGT)                                   SES01000
      VB=VN-AB*ALD                                                     SES01010
      PB=PA+PBBAR                                                      SES01020
      AMB=RHOA*VB/(PB/PA)**(GAMMA)                                     SES01030
      QIN=EN*(QIO-PBBAR)                                               SES01040
      AL=QIN*CN*SQRT(2.0*PBBAR/RHOA))                                  SES01050
      ZI(J)=ALD                                                        SES01060
      THETAI(J)=THETA                                                  SES01070
      AMBI(J)=AMB                                                      SES01080
      PBBARI(J)=PBBAR                                                  SES01090
C                                                                      SES01100
C     CALCULATE FORCES AND MOMENTS                                     SES01110
C                                                                      SES01120
      HPRES=-AB*PBBAR                                                  SES01130
      HBF=-AK1*ALD1*WS1                                                SES01140
      HBA=-AK2*ALD2*WS2                                                SES01150
      HSF=-PBBAR*ASEAL1                                                SES01160
      HSA=-(PBBAR+2.0)*ASEAL2                                          SES01170
      AKP1=-RHO*THETA*AKP*V*PI*2.0                                     SES01180
      AKP2=-RHO*THETA*AKP*V*V*PI*2.0                                   SES01190
      HPF=AKP1*WSPL1                                                   SES01200
      HPA=AKP2*WSPL2                                                   SES01210
      PPRES=-XCP*HPRES                                                 SES01220
      PBF=-AL5*HBF                                                     SES01230
      PBA=-AL6*HBA                                                     SES01240
      PPLAN=AL7*(HPF+HPA)                                              SES01250
      PLSF=AL3-XSEAL1/2.0                                              SES01260
      PLSA=AL4+XSEAL2/2.0                                              SES01270
      PSF=-HSF*PLSF                                                    SES01280
      PSA=HSA*PLSA                                                     SES01290
      IF(I.GE.1) GO TO 10                                              SES01300
      RES1=W+HBF+HBA+HSF+HSA+HPF+HPA+HPRES                             SES01310
      RES2=PBF+PBA+PSF+PSA+PPLAN+PPRES                                 SES01320
      ACCEL=RES1/AMASS                                                 SES01330
      PACCEL=RES2/AIYY                                                 SES01340
      IF(IILIST.NE.1) GO TO 6                                          SES01350
C                                                                      SES01360
C     LIST FORCES, MOMENTS, AND RESIDUALS                             SES01370
C                                                                      SES01380
      WRITE(6,9620) W,HBF,HBA,HSE,HSA,HPF,HPA,HPRES,RES1              SES01390
      WRITE(6,9625) PBF,PBA,PSF,PSA,PPLAN,PPRES,RES2                  SES01400
C     INPUT FINAL OPERATING POINT                                     SES01420
```

107

```
C
    6 I=1
      J=2
      READ(5,9510) WF,ALD,THETA,PBBAR                                   SES01430
      WRITE(6,9615) WF,ALD,THETA,PBBAR,V                                 SES01440
      AMASS=WF/G                                                         SES01450
      WSTEP=W-WF                                                         SES01460
      GO TO 5                                                            SES01470
C                                                                        SES01480
C     OUTPUT FORCES, MOMENTS, AND RESIDUALS AT FINAL OPER POINT          SES01490
C                                                                        SES01500
   10 RES1=WF+HBF+HBA+HSF+HSA+HPF+HPA+HPRES                              SES01510
      RES2=PBF+PBA+PSF+PSA+PPLAN+PPRES                                   SES01520
      IF(ILIST.NE.1) GO TO 11                                            SES01530
      WRITE(6,9620) WF,HBF,HBA,HSF,HSA,HPF,HPA,HPRES,RES1                SES01540
      WRITE(6,9625) PBF,PBA,PSF,PSA,PPLAN,PPRES,RES2                     SES01550
C                                                                        SES01560
C     INITIALIZE STATE VECTORS                                          SES01570
C                                                                        SES01580
   11 QPOINT(1)=ZI(1)*12.0                                               SES01590
      QPOINT(2)=ACCEL/G                                                  SES01600
      QPOINT(3)=THETAI(1)*RADEG                                          SES01610
      QPOINT(4)=PACCEL                                                   SES01620
      QPOINT(5)=AMBI(1)/RHOA                                             SES01630
      QPOINT(6)=PBBARI(1)                                                SES01640
      ALD0=ZI(1)*12.                                                     SES01650
      THETA0=THETAI(1)                                                   SES01660
      AMB0=AMBI(1)                                                       SES01670
      PBBAR0=PBBARI(1)                                                   SES01680
C                                                                        SES01690
C     COMPUTE SENSITIVITY COEFFICIENTS                                  SES01700
C                                                                        SES01710
      SIN31=SIN(31.0*DEGRAD)                                             SES01720
      SIN32=SIN(32.0*DEGRAD)                                             SES01730
C                                                                        SES01740
C     DERIVATIVES OF PBBAR AND MB                                       SES01750
C                                                                        SES01760
      DPBDZ=GAMMA*(AB-2.0*ABDIFF*ALD/BUBHGT)*PB/VB                       SES01770
      DPBMB=GAMMA*PB/AMB                                                 SES01780
      DMBPB=-RHOA*(EN+CN*AL/(RHOA*SQRT(2.0*PBBAR/RHOA)))                 SES01790
      DMBZ=DMBPB*DPBDZ                                                   SES01810
      DMBMB=DMBPB*DPBMB                                                  SES01820
C                                                                        SES01830
C     DERIVATIVES OF HEAVE FORCES W/RESPECT TO Z                        SES01840
C                                                                        SES01850
      DHBFZ=-AK1*((ALD-AL5*THETA)/TAN(DR1)+WS10)                         SES01860
      DHBAZ=-AK2*((ALD+AL6*THETA)/TAN(DR2)+WS20)                         SES01870
      DHBZ=(DHBFZ+DHBAZ)                                                 SES01880
```

108

```
      DHSFZ=-AK3*PBBAR-AK3*(ALD-AL3*THETA)*DPBDZ                         SES01910
      DHSAZ=-AK4**(PBBAR+2.)-AK4*(ALD+AL4*THETA)*DPBDZ                   SES01920
      DHSZ=DHSFZ+DHSAZ                                                   SES01930
      DHPBZ=-AB*DPBDZ                                                    SES01940
      DZZ=(DHBZ+DHSZ+DHPBZ)/AMASS                                       SES01950
C                                                                       SES01960
C     DERIVATIVES OF HEAVE FORCES W/RESPECT TO THETA                    SES01970
C                                                                       SES01980
      DHBFTH=AL1*AL5*RHO*G*((ALD-AL5*THETA)/TAN(DR1)+WS10)              SES01990
      DHBATH=-AL2*AL5*RHO*G*((ALD-AL5*THETA)/TAN(DR2)+WS20)             SES02000
      DHSFTH=AK3*AL3*PBBAR                                               SES02010
      DHSATH=-AK4*AL4*(PBBAR+2.0)                                        SES02020
      DHPFTH=-RHO*AKP*V*WSPL1*PI                                         SES02030
      DHPATH=-RHO*AKP*V*V*WSPL2*PI                                       SES02040
      DHBTH=DHBFTH+DHBATH                                                SES02050
      DHSTH=DHSFTH+DHSATH                                                SES02060
      DHPTH=DHPFTH+DHPATH                                                SES02070
      DZTH=(DHBTH+DHSTH+DHPTH)/AMASS                                     SES02080
C                                                                       SES02090
C     DERIVATIVE OF HEAVE FORCE W/RESPECT TO MB                         SES02100
C                                                                       SES02110
      DHPBMB=-AB*DP3MB                                                   SES02120
      DHSFMB=-ASEAL1*DPBMB                                               SES02130
      DHSAMB=-ASEAL2*DPBMB                                               SES02140
      DZMB=(DHPBMB+DHSFMB+DHSAMB)/AMASS                                  SES02150
C                                                                       SES02160
C     DERIVATIVES OF PITCH MOMENTS W/RESPECT TO THETA                   SES02170
C                                                                       SES02180
      DPBFTH=-AL5*DHBFTH                                                 SES02190
      DPBATH=AL6*DHBATH                                                  SES02200
      DPBTH=DPBFTH+DPBATH                                                SES02210
      DPPLTH=AL7*(DHPFTH+DHPATH)                                         SES02220
      DPSFTH=-PBBAR*(PLSF*AL3*WIDTH/SIN31-ASEAL1/2.0*SIN31)             SES02230
      DPSATH=-PBBAR*(PLSA*AL4*WIDTH/SIN32-ASEAL2/2.0*SIN32)             SES02240
      DPSTH=(DPSFTH+DPSATH)                                              SES02250
      DTHTH=(DPBTH+DPPLTH+DPSTH)/AIYY                                    SES02260
C                                                                       SES02270
      DPDMP=-AKDMP*V                                                     SES02280
      DTHDTH=DPDMP/AIYY                                                  SES02290
C                                                                       SES02300
C     DERIVATIVES OF PITCH MOMENTS W/RESPECT TO Z                       SES02310
C                                                                       SES02320
      DPBFZ=-AL5*DHBFZ                                                   SES02330
      DPBAZ=AL6*DHBAZ                                                    SES02340
      DPPBZ=-XCP*DHPBZ-ALDIFF*HPRES/(2.0*BUBHGT)                        SES02350
      DPSFZ=PBBAR*(PLSF*WIDTH/SIN31-ASEAL1/(2.0*SIN31))                 SES02360
      DPSAZ=-PBBAR*(PLSA*WIDTH/SIN31+ASEAL2/(2.0*SIN32))                SES02370
                                                                        SES02380
```

109

```
      DPSFPZ=ASEAL1*PLSF*DPBDZ
      DPSAPZ=-ASEAL2*PLSA*DPBDZ
      DPSFZ=DPSFZ+DPSFPZ
      DPSAZ=DPSAZ+DPSAPZ
      DPSZ=(DPSFZ+DPSAZ)
      DPBZ=DPBFZ+DPBAZ
      DTHZ=(DPSZ+DPBFZ+DPPBZ)/AIYY
C
C     DERIVATIVE OF PITCH MOMENT W/RESPECT TO MB
C
      DPPBMB=-XCP*DHPBMB
      DPSFMB=-PLSF*DHSFMB
      DPSAMB=PLSA*DHSAMB
      DTHMB=(DPPBMB+DPSFMB+DPSAMB)/AIYY
C
C     LIST THE VARIOUS SENSITIVITY COEFFICIENTS
C
      IF(ILIST.NE.1) GO TO 12
      WRITE(5,9640) DHBFZ,DHBAZ,DHSFZ,DHSAZ,DHPBZ,DHBFTH,
     1DHBATH,DHSFTH,DHSATH,DHPFTH,DHPATH,DHPBMB,
     2DHSFMB,DHSAMB
      WRITE(6,9645) DPBFTH,DPBATH,DPPLTH,DPSFTH,DPSATH,DPBFZ,DPBAZ,
     1DPSFZ,DPSAZ,DPBZ,DPBMB,DPSFMB,DPSAMB,DTHDTH
      WRITE(6,9650) DPBFZ,DPBMB,DMBPB,DMBPZ,DMBMB,DTHMB,
     1DMBZ,DZDTH,DZZ,DZTH,DZMB,DTHZ,DTHTH,DTHMB
      WRITE(6,9630) DZZ,DZTH,DZMB,DPBMB,
     1DMBMB,DMBMB,DPBDZ,DPBMB
C
C     PREPARE FOR TIME DOMAIN SOLUTION
C
C     COMPUTE VARIABLES FOR INTEGRATION SUBROUTINE
C
   12 RANGE=TF-TI
      ACCEL=ACCEL-WSTEP/AMASS
      QPOINT(2)=ACCEL/G
      H=RANGE/NSTEP
      T=TI
      NPASS=IFIX(FLOAT(NSTEP)/FLOAT(NPTS))
      IP=1
C
C     LOAD INITIAL CONDITIONS INTO OUTPUT MATRIX
C
      DO 15 I=1,NORD
      OUTVEC(IP,I)=QPOINT(I)
   15 CONTINUE
      TIME(IP)=T
      ICOUNT=NPTS
      NPTS=1
```

SES02390
SES02400
SES02410
SES02420
SES02430
SES02440
SES02450
SES02460
SES02470
SES02480
SES02490
SES02500
SES02510
SES02520
SES02530
SES02540
SES02550
SES02560
SES02570
SES02580
SES02590
SES02600
SES02610
SES02620
SES02630
SES02640
SES02650
SES02660
SES02670
SES02680
SES02690
SES02700
SES02710
SES02720
SES02730
SES02740
SES02750
SES02760
SES02770
SES02780
SES02790
SES02800
SES02810
SES02820
SES02830
SES02840
SES02850
SES02860

110

```
C
C     COMMENCE THE TIME DOMAIN SOLUTION
C
      MORD=5
25    CALL DEQRKF(MORD)
      NPTS=NPTS+1
      QPOINT(1)=ALDJ+X(1)*12.0
      QPOINT(2)=XDOT(2)/G
      QPOINT(3)=(THETA0+X(3))*RADEG
      QPOINT(4)=XDOT(4)*RADEG
      QPOINT(5)=(AMB0+X(5))/RHOA
      QPOINT(6)=PBBAR0+X(6)
      IP=IP+1
      TIME(IP)=T
      DO 30 I=1,NORD
      OUTVEC(IP,I)=QPOINT(I)
30    CONTINUE
      IF(NPTS.LT.(ICOUNT+1)) GO TO 25
C
C     OUTPUT THE TIME DOMAIN SOLUTION RESULTS
C
      K=0
      WRITE(6,9600)
      WRITE(6,9605)
      DO 35 I=1,NPTS
      K=K+1
      WRITE(6,9660) TIME(I),(OUTVEC(I,J),J=1,NORD)
      IF(K.LT.70) GO TO 35
      WRITE(6,9600)
      WRITE(6,9655)
      K=0
35    CONTINUE
C
C     PREPARE TO PLOT OUTPUT DATA
C
      DO 85 I=1,NORD
      WRITE(6,9600)
      DO 40 J=1,NPTS
      PLOTV(J)=OUTVEC(J,I)
40    CONTINUE
C     CHECK FOR PLOTP OR VERSATEC PLOTTING DESIRED
C
      IF(IPLOT.NE.1) GO TO 44
      IF(I.EQ.5) GO TO 85
      CALL VERSAP(NPTS,TIME,PLOTV)
      GO TO 35
44    CALL PLOTP(TIME,PLOTV,NPTS,0)
```

111

```fortran
      GO TO (45,50,55,60,65,70),I                                       SES03290
45    WRITE(6,9665)                                                     SES03300
      GO TO (86,9670)                                                   SES03310
50    WRITE(6,9675)                                                     SES03320
      GO TO (86,9680)                                                   SES03330
55    WRITE(6,9680)                                                     SES03340
60    WRITE(6,9680)                                                     SES03350
      GO TO (86,9685)                                                   SES03360
65    WRITE(6,9685)                                                     SES03370
      GO TO (36,9695)                                                   SES03380
70    WRITE(6,9695)                                                     SES03390
80    WRITE(6,9605)                                                     SES03410
85    CONTINUE                                                          SES03420
      WRITE(6,9600)                                                     SES03430
9500  FORMAT(2F10.1,2I10)                                               SES03440
9505  FORMAT(5F10.4)                                                    SES03450
9510  FORMAT(4F10.4)                                                    SES03460
9600  FORMAT(1H1)                                                       SES03470
9605  FORMAT(//,20X,'TWO-DEGREE OF FREEDOM CAB SES LINEAR MODEL',/)     SES03480
9610  FORMAT('NO OF OUTPUT POINTS = ',I16,/,1X,'TF = ',F10.1,/,1X,      SES03490
     1'NO OF INTEGRATION STEPS = ',                                     SES03500
9615  FORMAT(/,1X,'OPERATING CONDITION ',/,/,1X,'PITCH ',               SES03510
     1'WEIGHT = ',F10.4,/,1X,'DRAFT = ',F10.4,/,1X,                     SES03520
     2'ANGLE = ',F10.4,/,1X,'PLENUM PRESSURE = ',F10.4,/,1X,            SES03530
     3'SPEED = ',F10.4,                                                 SES03540
9620  FORMAT(/,5X,'HBA',7X,'HBF',7X,'HSA',7X,'HSF',/,1X,                SES03550
     1'HPF = ',8X,'HPA',7X,'RES1',/,1X,9F10.4)                          SES03560
9625  FORMAT(/,6X,'RES2',7X,'PBA',6X,'PSA',6X,'PPLAN',6X,               SES03570
     1'PPRES = ',1X,7E10.4)                                             SES03580
9630  FORMAT(/,1X,'DZZ = ',E11.4,/,1X,'DZFH = ',E11.4,/,1X,             SES03590
     1'DZMB = ',E11.4,/,1X,'DTHFH = ',E11.4,/,1X,'DTHMB = ',E11.4,      SES03600
     2'DTHZ = ',E11.4,/,1X,                                             SES03610
     3'DMBZ = ',E11.4,/,1X,                                             SES03620
     4'DMBMB = ',E11.4,/,1X,'DPBMB = ',E11.4,/,1X,'DPBDZ = ',E11.4)     SES03630
     5'DDPBDZ = ',E11.4,                                                SES03640
9640  FORMAT(1X,'HEAVE SENSITIVITY COEFFICIENTS',//,1X,                 SES03650
     1'DHBFZ = ',E11.4,/,1X,'DHBAZ = ',E11.4,/,1X,'DHSFZ = ',           SES03660
     2'E11.4,/,1X,'DHSAZ = ',E11.4,/,1X,                                SES03670
     3'DHPBZ = ',E11.4,/,1X,'DHBFTH = ',E11.4,/,1X,'DHBATH = ',         SES03680
     4'DHBATH = ',E11.4,/,1X,'DHSFTH = ',E11.4,/,1X,'DHSATH = ',        SES03690
     5'E11.4,/,1X,'DHPFTH = ',E11.4,/,1X,'DHPAFH = ',E11.4,/,1X,        SES03700
     7'DHPBMB = ',E11.4,/,1X,'DHSFMB = ',E11.4,/,1X,'DHSAMB = ',        SES03710
     8'E11.4,                                                           SES03720
9645  FORMAT(/,1X,'PITCH SENSITIVITY COEFFICIENTS',//,1X,               SES03730
     1'DPBFTH = ',E11.4,/,1X,'DPBATH = ',E11.4,/,1X,                    SES03740
     2'DPPLTH = ',E11.4,/,1X,'DPSFTH = ',E11.4,/,1X,                    SES03750
```

112

```
     3'DPSATH = ',E11.4,/,1X,'DPBPZ = ',E11.4,/,1X,'DPBAZ = ',       SES03770
     4 E11.4,/,1X,'DPSFZ = ',E11.4,/,1X,'DPSAZ = ',E11.4,/,1X,        SES03780
     6'DPPBZ = ',E11.4,/,1X,'DPPBMB = ',E11.4,/,1X,                   SES03790
     7/,1X,'DPSFMB = ',E11.4,/,1X,'DPSAMB = ',E11.4,                  SES03800
     8/,1X,'DTHDTH = ',E11.4)                                         SES03810
9650 FORMAT(/,1X,'PLENUM PRESSURE AND MASS SENS. COEFF.',//,1X,       SES03820
     1'DPBDZ = ',E11.4,/,1X,'DPBMB = ',E11.4,/,1X,'DMBPB = ',E11.4,   SES03830
     2 E11.4,/,1X,'DMBZ = ',E11.4,/,1X,'DMBMB = ',E11.4)              SES03840
9655 FORMAT(/,7X,'TIME',7X,'DRAFT(IN) ACCEL(G)',2X,'THETA(DEG) THETADDOT' SES03850
     1'VM(CU-FT)',8X,'PBBAR',1X,F10.4)                                SES03860
9660 FORMAT(1X,'PLOT IS DRAFT(IN) VS TIME')                          SES03870
9665 FORMAT(1X,'PLOT IS CG ACCELERATION(GEES) VS TIME')              SES03880
9670 FORMAT(1X,'PLOT IS PITCH ANGLE (DEG) VS TIME')                  SES03890
9675 FORMAT(1X,'PLOT IS PITCH ACCEL (DEG/SEC2) VS TIME')             SES03900
9680 FORMAT(1X,'PLOT IS VMASS(FT3) VS TIME')                         SES03910
9685 FORMAT(1X,'PLOT IS PBBAR (LBF/FT3) VS TIME')                    SES03920
9695                                                                  SES03930
     STOP                                                             SES03940
     END                                                             SES03950
C                                                                    SES03960
     SUBROUTINE DE2RKF(NORD)                                         SES03970
C                                                                    SES03980
C    PURPOSE: GENERATE THE SOLUTIONS OF A SYSTEM OF SIMULTANEOUS     SES03990
C    FIRST ORDER DIFFERENTIAL EQUATIONS USING A FOUR-POINT FIXED-    SES04000
C    STEP RUNGE-KUTTA ALGORITHM.                                     SES04010
C                                                                    SES04020
C    INITIAL BOOKKEEPING SECTION                                     SES04030
C                                                                    SES04040
     DIMENSION XI(6),P(6),Q(6),R(6),S(6)                             SES04050
     COMMON/INTEG/X(6),XDOT(6),T,H,NPASS                             SES04060
     REAL*8 P,Q,R,S,KDP                                              SES04070
     NTERM=0                                                         SES04080
     KDP=0.5D0                                                       SES04090
     NITER=0                                                         SES04100
C                                                                    SES04110
C    CALL SUBROUTINE DYNMIC TO EVALUATE THE DERIVITIVES AT TIME T    SES04120
C                                                                    SES04130
05   CALL DYNMIC                                                     SES04140
C                                                                    SES04150
C    BEGIN RUNGE-KUTTA SOLUTION                                      SES04160
C                                                                    SES04170
     NTERM=NTERM+1                                                   SES04180
     GO TO (6,15,25,35),NTERM                                        SES04190
C                                                                    SES04200
C    SAVE X(I),COMPUTE P(I) AND X(I) +0.5*P(I)                       SES04210
C                                                                    SES04220
6    DO 10 I=1,NORD                                                  SES04230
     XI(I)=X(I)                                                      SES04240
```

113

```
      P(I)=XDOT(I)*H
      X(I)=X(I)+P(I)*KDP                                          SES04250
   10 CONTINUE                                                    SES04260
      T=T+H*KDP                                                   SES04270
      GO TO 5                                                     SES04280
C                                                                 SES04290
C     COMPUTE Q(I) AND X(I)+0.5*Q(I)                              SES04300
C                                                                 SES04310
      DO 20 I=1,NORD                                              SES04320
      Q(I)=XDOT(I)*H                                              SES04330
      X(I)=X(I)+Q(I)*KDP                                          SES04340
   20 CONTINUE                                                    SES04350
      T=T+H*KDP                                                   SES04360
      GO TO 5                                                     SES04370
C                                                                 SES04380
C     COMPUTE R(I) AND X(I)+R(I)                                  SES04390
C                                                                 SES04400
      DO 30 I=1,NORD                                              SES04410
      R(I)=XDOT(I)*H                                              SES04420
      X(I)=X(I)+R(I)                                              SES04430
   30 CONTINUE                                                    SES04440
      T=T+H*KDP                                                   SES04450
      GO TO 5                                                     SES04460
C                                                                 SES04470
C     COMPUTE S(I) AND X(I+H)                                     SES04480
C                                                                 SES04490
      DO 40 I=1,NORD                                              SES04500
      S(I)=XDOT(I)*H                                              SES04510
      X(I)=X(I)+(1./6.)*(P(I)+2.*Q(I)+2.*R(I)+S(I))               SES04520
   40 CONTINUE                                                    SES04530
      NITER=NITER+1                                               SES04540
      NTERM=0                                                     SES04550
      IF(NITER.LT.NPASS) GO TO 05                                 SES04560
      RETURN                                                      SES04570
      END                                                         SES04580
C                                                                 SES04590
C     SUBROUTINE DYNMIC                                           SES04600
C                                                                 SES04610
C     PURPOSE:  TO EVALUATE THE STATE VARIABLE DERRIVATIVES       SES04620
C                                                                 SES04630
      COMMON/DERIV/DZZ,DZTH,DZMB,DTHZ,DTHTH,DTHMB,DTHDTH,DMBMB,DMBZ, SES04640
     1DPBDZ,DPBMB,ACCEL,PACCEL                                    SES04650
      COMMON/INTEG/X(6),XDOT(6),T,H,NORD,NPASS                    SES04660
C                                                                 SES04670
C     EVALUATE THE STATE MATRIX AND OUTPUT VARIABLE               SES04680
C                                                                 SES04690
      XDOT(1)=X(2)                                                SES04700
      XDOT(2)=DZZ*X(1)+DZTH*X(3)+DZMB*X(5)+ACCEL                  SES04710
      XDOT(3)=X(4)                                                SES04720
```

114

```
      XDOT(4)=DTHZ*X(1)+DTHTH*X(3)+DTHMB*X(5)+DTHDTH*X(4)+PACCEL      SES04730
      XDOT(5)=DMBZ*X(1)+DMBMB*X(5)                                   SES04740
      X(6)=DPBDZ*X(1)+DPBMB*X(5)                                     SES04750
      RETURN                                                         SES04760
      END                                                            SES04770
      SUBROUTINE VERSAP(NUMPTS,X,Y)
      DIMENSION X(300),Y(300),RTB(12),ITB(28)
      EQUIVALENCE(TITLE,RTB(5))
      REAL*8 TITLE(12)
      READ(5,9515) TITLE
9515  FORMAT(6A8)
      RTB(1)=00.00
      RTB(2)=00.00
      RTB(3)=00.0
      RTB(4)=00.0
      DO 1 I=1,12
1     ITB(I)=0
      ITB(3)=6
      ITB(4)=7
      CALL DRAWP(NUMPTS,X,Y,ITB,RTB)
      RETURN
      END
```

LIST OF REFERENCES

1. Leo,D.G.,and Boncal,R.,<u>XR-3 Surface Effects Ship Test Craft: A Mathematical Model and Simulation Program with Verification</u>, M.S. Thesis, U. S. Naval Post Graduate School, Monterey, California, 1973

2. Forbes,<u>Validation of the Six Degree of Freedom Mathematical Model of the XR-3 in Calm Water</u>,M.S. Thesis, Naval Postgraduate School, Monterey, California, 1974

3. Menzel, R.F.,<u>Study of the Rool and Pitch Transients in calm Water using the Simulated Performance of the XR-3 Loads and Motions Program</u> ,M.S. Thesis, Naval Postgraduate School, Monterey, California,1975

4. Finley,R.A.,<u>Refinements of the Seal Subroutines and Fan Air Maps for the XR-3 Loads and Motions Program</u>,M.S. Thesis, Naval Postgraduate School, Monterey, California, 1974

5. Riedel,R.G.,<u>Sensitivity Stude of the XR-3 Loads and Motions Computer Program Sidewall Parameters and forces on Roll Behavior in Calm Sea and a Comparison ro Testcraft Turn Maneuver Behavior</u>, M.S. Thesis, Naval Postgraduate School, 1977

6. Grant,U.S.,Jr.,<u>Study of Heave Acceleration/Velocity Control for the Surface Effect Ship</u>,M.S. Thesis, Naval Post Graduate School, 1974

7. McIntyre,L.F.,_Investigation of a Linear Two-Degree-of-freedom Simulation for the XR-3 Captured Air Bubble(CAB) Craft in the Frequency Domain_,M.S. Thesis, Naval Postgraduate School,1977

8. Rhor Marine Inc.,Report TT00013A,_Stability and Maneuverability Report_,by E. H. Price, R. C. Stoner, and N. L. Wener, p. 2-2,31 August 1978

9. Department of the Navy,_Surface Effects Ship Aero/Hydrodynamics Technology Design Manual_,SES Project PMS-304, Vol. II, February 1976.

10. Naval Postgraduate School, Report NPS67-78-001PR,_Seal Loads of the Surface Effect Ship Testcraft XR-3_,D.M. Layton, P 43, November 1977.

11. Moloney,R.W.,_The Effect of Seal Shape Variations Upon the Performance of the XR-3 Captured Air Bubble Testcraft_,M.S. Thesis,Naval Postgraduate School, Monterey, California,1975

12. Riedel, R.G.,_project EE 4900_,Project report to Professer A. Gerba Jr., Naval Postgraduate School, June, 1977.

13. Barnaoy, K. G., _Basic Naval Architecture_,Fifth Edition, p. 336-339, Hutchinson Scientific and Technical, London, 1967.

14. Naval Postgraduate School, Report NPS62-78-008PR, _Sensitivity Analysis of the XR-3 Heave Equations to Changes in Plenum Air Leakage and Influx Rates_, A Gerba Jr.,and G. J. Thaler, p 28, and 54-57, September 1978.

INITIAL DISTRIBUTION LIST

No. Copies

1. Defense Documentation Center   2
   Cameron Station
   Alexandria Virginia 22314

2. Library, Code 0142   2
   Naval Postgraduate School
   Monterey, California 93940

3. Department Chairman, Code 62   1
   Department of Electrical Engineering
   Naval Postgraduate School
   Monterey, California 93940

4. Professor Alex Gerba, Jr., Code 52Gz   5
   Department of Electrical Engineering
   Naval Postgraduate School
   Monterey California 93940

5. Professor George J. Thaler, Code 52Tr   5
   Department of Electrical Engineering
   Naval Postgraduate School
   Monterey, California 93940

6. Proffessor D. M. Layton, Code 67Ln   1
   Department of Aeronautics
   Naval Postgraduate School
   Monterey California 93940

7. Mr. H. Robertson   6
   PMS 304, Code 141
   Surface Effects Ships Project Office
   PO Box 34401
   Bethesda, Maryland 20034

8. Lt Leslie W. Barnes, USN   1
   Route 7, Box 412E
   Tucson, Arizona 85706